V2-20.0-0-FSP-SM ✓ ACTIVE

Raychem | Raychem Versafit V2

TE Internal #: 757543J001

Raychem Versafit V2, Heat Shrink Tubing, Black, Single Wall Type,

21.4 Expanded Inside Diameter (Min) .842 Expanded Inside

Diameter (Min)

View on TE.com >



Heat Shrink Tubing



Primary Product Color: Black

Wall Type: Single

Expanded Inside Diameter (Min): 21.4 mm [.842 in]

Recovered Inside Diameter (Max): 10.01 mm [.394 in]

Shrink Ratio: 2:1

Features

Product Type Features

Wall Type Single	
Product Family V2	

Electrical Characteristics

Voltage (Max)	.6 kV	
Voltage (Maxy	.o kv	

Body Features

Primary Product Color	Black
Shrink Ratio	2:1
Primary Product Material	Irradiated Modified Polyolefin
Flexibility	Very Flexible

Dimensions

Recovered Wall Thickness (Tolerance)	.76 mm[.03 in]
Expanded Inside Diameter (Min)	21.4 mm[.842 in]
Recovered Inside Diameter (Max)	10.01 mm[.394 in]

Usage Conditions

Fluid Resistance	None
Shrink Temperature (Min)	70 °C
Heat Shrink Tubing Flammability	Highly Flame-Retardant
Operating Temperature Range	-30 – 125 °C



Heat Shrink Tubing Resistance	Strain, Wrinkling
Recovery Temperature	90 °C
Product Availability	
Applicable Region	Global
Packaging Features	
Packaging Method	Flat Spool
Other	
Meets Low Outgassing Requirements	No
Product Source	China, US

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






TE Part # CJ2087-000 HL2010E-KIT-120V



CV1981-ST-230V1600W-EU

Also in the Series | Raychem Versafit V2



Customers Also Bought



TE Part #1-353717-2 DYNAMIC 3000 CONTACT



TE Part #1-917808-2 DYNAMIC 5000 REC AND TAB HSG



TE Part #170048-2 110 FASTON,REC.,24-20 AWG,TPBR



TE Part #1-1903131-6

DYNAMIC 1200 REC AND TAB HSG



TE Part #1746741-3
RITS CONN. SOCKET ASSY 3P
YELLOW



TE Part #046571J001 V2-18.0-0-FSP-SM




TE Part #115607J001 V2-12.0-0-FSP-SM



TE Part #137963J001 V2-1.5-0-SP-SM



TE Part #985923J001 V2-6.0-0-SP-SM





Documents

Datasheets & Catalog Pages

VERSAFIT V2 Pages from 9-1773447-9

English

Application Tooling for Raychem Heat Shrink Product

English

Highly Flame-Retardant, Low Recovery Temp., Metric-Sized Heat-Shrinkable Tubing

English

Product Specifications

Quality Specification

English