### **HX-SCE**

TE Internal #: E76198-000

HX-SCE, Printable Tubing, Ladder Printable Tubing Type, Low Fire Hazard Printable Tubing Grade, 2:1 Printable Tubing Shrink Ratio,

Yellow

View on TE.com >



Identification & Labeling > Printable Tubing > HX-SCE LOW FIRE HAZARD SLEEVES



Printable Tubing Type: Ladder

Printable Tubing Grade: Low Fire Hazard

Printable Tubing Shrink Ratio: 2:1 Primary Product Color: Yellow

Markers per Sleeve: 1

### All HX-SCE LOW FIRE HAZARD SLEEVES (48)

### **Features**

### Product Type Features

Product Type Features	
Printable Tubing Type	Ladder
Printable Tubing Grade	Low Fire Hazard
Body Features	
Printable Tubing Shrink Ratio	2:1
Primary Product Color	Yellow
Markers per Sleeve	1
Dimensions	
Product Length	50 mm[2 in]
Supplied Inner Diameter	38.1 mm[1.5 in]
Recovered Inside Diameter	19 mm[.75 in]
Compatible Cable Diameter Range	20.9 – 33. mm[.825 – 1.3 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

See TE Document 411-121005 the Printer

Product Ribbon Matrix

Operation/Application

Recommended Ribbon



### Printer/Label Features

Recommended Printer	See TE Document 411-121005 the Printer Product Ribbon Matrix
Printer Technology	Thermal Transfer
Packaging Features	
Packaging Quantity	250

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





TE Part # 1-2186500-1 T3212-PRINTER






T3224-SWARE-PRINTER





## Also in the Series | HX-SCE



# Customers Also Bought







ZHTM: Heat Shrink Tubing, 2:1 Shrink

















## **Documents**

## **Product Drawings**

HX-SCE-38.1-50-4

English

## Datasheets & Catalog Pages

Technical Datasheet for HX-SCE Heat Shrink Marker Sleeves

English

### **IDENTIFICATION SELECTION GUIDE**

English

## **Product Specifications**

HX - LFH Heat Shrink Sleeving

English

### **Instruction Sheets**

Instruction Sheet (non U.S.)

English