ZHD-SCE-25.4-50-9 ✓ ACTIVE



ZHD-SCE

TE Internal #: EC9888-000

ZHD-SCE, Printable Tubing, Ladder Printable Tubing Type, Fluid Resistant & Low Fire Hazard Printable Tubing Grade, 2:1 Printable

Tubing Shrink Ratio

View on TE.com >



Identification & Labeling > Printable Tubing > ZHD-SCE LFH & FLUID RESISTANT SLEEVES



Printable Tubing Type: Ladder

Printable Tubing Grade: Fluid Resistant & Low Fire Hazard

Printable Tubing Shrink Ratio: 2:1 Primary Product Color: White

Markers per Sleeve: 1

All ZHD-SCE LFH & FLUID RESISTANT SLEEVES (88)

Features

Product Type Features

Product Type Features	
Printable Tubing Type	Ladder
Printable Tubing Grade	Fluid Resistant & Low Fire Hazard
Body Features	
Printable Tubing Shrink Ratio	2:1
Primary Product Color	White
Markers per Sleeve	1
Dimensions	
Product Length	50 mm[2 in]
Supplied Inner Diameter	25.4 mm[1 in]
Recovered Inside Diameter	12.7 mm[.5 in]
Compatible Cable Diameter Range	14.2 – 21.5 mm[.563 – .85 in]
Usage Conditions	
Operating Temperature Range	-55 – 135 °C[-67 – 275 °F]
Operation/Application	

See TE Document 411-121005 the Printer

Product Ribbon Matrix

Recommended Ribbon



Printer/Label Features

Recommended Printer	See TE Document 411-121005 the Printer Product Ribbon Matrix
Printer Technology	Thermal Transfer
Packaging Features	
Packaging Quantity	250

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # 1-2186500-1 T3212-PRINTER



TE Part # 1-2186502-1 TE Part # 1-2186503-1 T3224-PRINTER T3224-SWARE-PRINTER





Also in the Series | ZHD-SCE



Customers Also Bought



ZHD-SCE LFH & FLUID RESISTANT SLEEVES



TE Part #2-323136-1 SOLIS SPDFLG 22-16COM22-18MIL6



TE Part #1958311-1 TERMINAL, SOLIS R 3/0 10.75mm





TE Part #5039294018 Single Wall DR 25: Heat Shrink Tubing, 2:1 Shrink Ratio



TE Part #1062-16-0122 DEUTSCH STAMPED & FORMED CONTACTS



TE Part #3-641240-7 Nylon Gold Plated Receptacle: 2.54 mm, No Mating Alignment, MTA 100









Documents

Product Drawings

ZHD-SCE-25.4-50-9

English

Datasheets & Catalog Pages

TTDS for ZHD-SCE, LOW FIRE HAZARD, DIESEL RESISTANT

English

Product Specifications

Product Specification

English