

Raychem | Raychem ELB

TE Internal #: EE5634-000

Raychem ELB, Loadbreak Connections, AMERICAS, Cold Applied, ≤ 25 kV, Compression, 200A Bushing Type, Aluminum/Copper

View on TE.com >



Energy & Power > Power Cable Accessories > Separable Connectors > Loadbreak Connections > LOADBREAK 200A INSULATING CAP





Loadbreak Connection Product Availability: AMERICAS

Loadbreak Connection Technology: Cold Applied
Loadbreak Connection Voltage Class: ≤ 25 kV

Loadbreak Connection Connector Type: Compression

Bushing Type: 200A

All LOADBREAK 200A INSULATING CAP (3)

Features

Product Type Features

Loadbreak Connection Technology	Cold Applied
Loadbreak Connection Connector Type	Compression
Bushing Type	200A
Electrical Characteristics	
Loadbreak Connection Voltage Class	≤ 25 kV
Body Features	
Loadbreak Connection Conductor Material	Aluminum/Copper
Operation/Application	
Application Type	Insulating Cap
Industry Standards	
UL Rating	No
Product Availability	
Loadbreak Connection Product Availability	AMERICAS

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JUN 2018 (191) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts










Also in the Series | Raychem ELB





Dead Break Connections(1)



Customers Also Bought



TE Part #7-1423162-5 7022ACX=RLY,STD,OFF,2P,120VAC, 15SEC,X OP



TE Part #BM1541-000 Load Break Elbow: 200A, 15 and 25 kV

















Documents

Product Drawings ELB-25-200-IC

English

Datasheets & Catalog Pages 200A INSULATING CAP RAYCHEM

English