# 1-2198325-7 ACTIVE

TE Internal #: 1-2198325-7

SFP/SFP+/zSFP+, Cage Assembly with Integrated Connector, Data


Rate (Max) 32 Gb/s, Elastomeric Gasket, SFP+ Thermally Enhanced,

Included Lightpipe

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > SFP/SFP+/zSFP+ > zSFP+ Stacked Cage Assembly: Gasket



Pluggable I/O Product Type: Cage Assembly with Integrated Connector

Data Rate (Max): 32 Gb/s

EMI Containment Feature Type: Elastomeric Gasket
Pluggable I/O Applications: SFP+ Thermally Enhanced

Included Lightpipe: Yes

All zSFP+ Stacked Cage Assembly: Gasket (40)

### **Features**

### **Product Type Features**

Form Factor	zSFP+ Stacked (SFP28)
Cage Type	Stacked
Pluggable I/O Product Type	Cage Assembly with Integrated Connector
Integrated Lightpipes	Yes
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

### **Configuration Features**

Port Matrix Configuration	2 x 2
Lightpipe Configuration	Three
Lightpipe Style	Standard
Number of Ports	4
Number of Positions	80

### **Electrical Characteristics**

Data Rate (Max)	32 Gb/s
, , , ,	

#### **Contact Features**

Tail Plating Material	Tin	
-----------------------	-----	--



Contact Mating Area Plating Thickness	.76 μm[29.92 μin]
Contact Mating Area Plating Material	Gold or Gold Flash over Palladium Nickel
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
PCB Mounting Style	Through Hole - Press-Fit
Connector Mounting Type	Board Mount
Housing Features	
Cage Material	Nickel Silver Alloy
Centerline (Pitch)	.8 mm[.032 in]
Dimensions	
PCB Thickness (Recommended)	1.5 mm[.059 in]
Tail Length	1.8 mm[.07 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Heat Sink Compatible	No
For Use With Pluggable I/O Products	zSFP+ SMT Connector
Pluggable I/O Applications	SFP+ Thermally Enhanced
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Tray
Other	
EMI Containment Feature Type	Elastomeric Gasket
Included Lightpipe	Yes
Product Compliance  For compliance documentation, visit the product page on TE.com>	

Not Yet Reviewed

EU RoHS Directive 2011/65/EU



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: DEC 2014 (161) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

### **Compatible Parts**





















TE Part # CAT-C11-G28 SFP56 to SFP56 Cable Assembly: 26 AWG



TE Part # 2821262-1 SFP28 DIRECT ATTACH CA, 0.5M, 33AWG



TE Part # 4-2334985-2 SFP56 DIRECT ATTACH CA, 1M, 32AWG



TE Part # CAT-C11-N490111

SFP28 to SFP28 Cable Assembly: 28

AWG



TE Part # 2821262-2 SFP28 DIRECT ATTACH CA, 1.0M, 33AWG



TE Part # 2821262-3
SFP28 DIRECT ATTACH CA, 1.5M, 33AWG



TE Part # 2821262-4 SFP28 DIRECT ATTACH CA, 2.0M, 33AWG

## Customers Also Bought



TE Part #2328118-3 LUMAWISE ENDURANCE N OPEN CAP ASSEMBLY



TE Part #2132529-3 IMP100S,H,V3P6C,LG,REW39,5.5



TE Part #1470108-6 AMP HPI 2.0MM HEADERS



TE Part #YDTS26T23-53SNV001 D38999: Straight Plug, 23-53 Insert



TE Part #1734100-3 Champ050 series,30pos,Au over PdNi



TE Part #1734101-3 Champ050 series,30pos,Au over PdNi



TE Part #1757256-1 SMPM FEMALE BULLET ADAPTER



TE Part #1934949-1 Tinman 5pr 8col vert recpt 15mm stack



TE Part #2007808-2 IMP100S,H,V4P10C,LG,OEW46,4.9



TE Part #2110570-1 SFP+ 1x4 Cage Assembly Square Light Pipe

### **Documents**



### **Product Drawings**

zSFP+ STACKED 2x2 RECEPTACLE ASSEMBLY

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-2198325-7\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2198325-7\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2198325-7\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

zSFP+ Interconnect Brochure

English

### **Product Specifications**

**Application Specification** 

English

### **Instruction Sheets**

Instruction Sheet (U.S.)

English

Instruction Sheet (U.S.)

English