2-1904011-2 <

Power Relay B

TE Internal #: 2-1904011-2 Power Relay B, Mini Relays, 12VDC Rated Coil Voltage, 30 – 50 A, 1 Form A (NO), Plug-In, 85Ω Mini Relay Coil Resistance View on TE.com >



Relays, Contactors & Switches > Relays > Automotive Relays > Automotive Plug-In Relays > Mini Relays



Rated Coil Voltage: 12 VDC Mini Relay Contact Current Class: 30 – 50 A Mini Relay Contact Arrangement: 1 Form A (NO) Mini Relay Mounting Type: Plug-In Mini Relay Coil Resistance: 85 Ω

Features

Product Type Features

Relay Type	Power Relay B
Electrical Characteristics	
Current Rating (85°C)	30 A
Coil Power Rating Class	>1.5W W
Contact Limiting Short-Time Current	210 A
Insulation Initial Dielectric Between Contacts and Coil	500 Vrms
Insulation Initial Dielectric Between Coil/Contact Class	0 – 500 V
Insulation Initial Dielectric Between Open Contacts	500 Vrms
Coil Magnetic System	Monostable, DC
Contact Limiting Making Current	120 A
Coil Power Rating (DC)	1700 mW
Contact Limiting Continuous Current	50 A
Rated Voltage	12 VDC
Contact Limiting Breaking Current	30 A
Contact Switching Load (Min)	1000mA @ 5VDC
Rated Coil Voltage	12 VDC
Mini Relay Coil Resistance	85 Ω
Body Features	
Weight	35 g[1.2 oz]

2-1904011-2

Power Relay B, Mini Relays, 12VDC Rated Coil Voltage, 30 – 50 A, 1 Form A (NO), Plug-In, 85Ω Mini Relay Coil Resistance



Contact Features

Terminal Type	Plug-In, Quick Connect
Contact Base Material	Ag Alloy
Mini Relay Contact Current Class	30 – 50 A
Mini Relay Contact Arrangement	1 Form A (NO)
Mechanical Attachment	
Mini Relay Mounting Type	Plug-In
Dimensions	
Width Class (Mechanical)	25 – 30 mm
Height	26 mm[1.024 in]
Length	28.5 mm[1.122 in]
Length Class (Mechanical)	25 – 30 mm
Width	28.5 mm[1.122 in]
Height Class (Mechanical)	25 – 30 mm
Usage Conditions	
Environmental Ambient Temperature Class	105 – 125°C
Environmental Ambient Temperature (Max)	125 °C[257 °F]

Other

Mounting Brackets	Without
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

2-1904011-2

Power Relay B, Mini Relays, 12VDC Rated Coil Voltage, 30 – 50 A, 1 Form A (NO), Plug-In, 85Ω Mini Relay Coil Resistance



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Also in the Series | Power Relay B



Mini Relays(23)

Customers Also Bought



2-1904011-2

Power Relay B, Mini Relays, 12VDC Rated Coil Voltage, 30 – 50 A, 1 Form A (NO), Plug-In, 85Ω Mini Relay Coil Resistance





Documents

Product Drawings

CAD Files 3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1904011-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1904011-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1904011-2_A.3d_stp.zip

English

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

Power Relay B, Mini ISO, Plug-In

English

Product Specifications Definitions, Handling, Processing, Testing and Use of Relays

English