



RCBO, 6 kA, 3P Type A, 30 mA, B-Char, In: 13A Un: 400V

Model	
product brand name	SENTRON
product designation	RCBO
design of the product	Instantaneous
General technical data	
number of poles	3
number of poles / with protection	3
tripping characteristic class	B
mechanical service life (switching cycles) / typical	10 000
overvoltage category	III
degree of pollution	3
Voltage	
type of voltage / of the operating voltage	AC
insulation voltage (Ui) / rated value	500 V
surge voltage resistance / rated value	4 000 V
surge current resistance / at (8/20) μ s	0.25 kA
Supply voltage	
supply voltage	
• at AC / rated value	400 V
• for testing equipment / minimum	340 V
operating frequency	50 Hz
supply voltage frequency / rated value	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Switching capacity	
breaking capacity short-circuit current (I _{cn}) / according to EN 61009-1 / rated value	6 kA
switching capacity current	
• acc. to EN 60898 / rated value	6 kA
• acc. to IEC 60947-2 / rated value	6 kA
rated residual switching capacity (I Δ m) / according to IEC 61009-1	4.5 kA
energy limitation class	3
Dissipation	
power loss [W]	
• maximum	2.5 W
Current	

tripping fault current / rated value	30 mA	
operational current		
• at 30 °C / rated value	13 A	
• at 40 °C / rated value	12.2 A	
• at 45 °C / rated value	11.7 A	
• at 50 °C / rated value	11.2 A	
• at 55 °C / rated value	10.8 A	
• at 60 °C / rated value	10.3 A	
• at AC / rated value	13 A	
residual current type	A	
Product details		
product function / neutral conductor switching	Yes	
product feature / touch protection	Yes	
product feature		
• halogen-free	No	
Connections		
connectable conductor cross-section / solid		
• maximum	35 mm ²	
connectable conductor cross-section / stranded		
• maximum	35 mm ²	
connectable conductor cross-section / finely stranded / with core end processing		
• maximum	35 mm ²	
tightening torque / with screw-type terminals		
• minimum	2 N·m	
• maximum	2 N·m	
position / of power supply cord	Either top or bottom	
Mechanical Design		
height	85 mm	
width	54 mm	
depth	72 mm	
installation depth	70 mm	
number of modular width units	3	
mounting position	Any	
net weight	404 g	
weight / with packaging	446 g	
Environmental conditions		
influence of the surrounding temperature	Max. 95% humidity	
ambient temperature / during operation		
• minimum	-25 °C	
• maximum	40 °C	
ambient temperature / during storage		
• minimum	-40 °C	
• maximum	70 °C	
number of test cycles / for environmental testing / acc. to IEC 60068-2-30	28	
Certificates		
reference code		
• acc. to DIN EN 61346-2	F	
• acc. to IEC 81346-2	F	
General Product Approval	Declaration of Conformity	other

[Miscellaneous](#)



[Miscellaneous](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1336-6FP13>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SU1336-6FP13>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1336-6FP13

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

