IN ACCORDANCE WITH SUB-SECTION 38.3

OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1. Name/Description of battery

Part no. 215617-01

1a. Name/Description of the cells inside the battery

1 cell

The test summary of the cells inside the battery must either be presented or under checkpoint 9 and 9a it must be confirmed that the UN 38.3 test summary for the cells is available.

2. Manufacture	2. Manufacturer of battery		
Name	Company confidential		
Address			
Phone			
Email			
Website			

2a. Manufacturer of the equipment (if the battery is contained in equipment)		
Name	Plantronics Inc. dba Poly	
Address	345 Encinal Street, Santa Cruz, California USA 95060	
Phone	800-544-4660 or 831-426-5858	
Email		
Website	poly.com/us/en	

3. Test laboratory of battery		
Name	ATS Electronic Technology Co., Ltd.	
Address	3/F, Building A, No. 1 Hedong Three Road, Jinxia Community, Changan, Donggue	
Phone	+86-769-38975958	
Email		
Website	www.dgats.com	

4. ID-number and date			
Unique test report identification number	ATSU190710611	Date of test report	2019August6



IN ACCORDANCE WITH SUB-SECTION 38.3

OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

Part no. 215617-01

DESCRIPTION OF BATTERY

5. M	ark the type of battery with an "•"	
\bigcirc	Lithium ion battery	Lithium metal battery
\bigcirc	Lithium hybrid battery	

6. Parameters	
Mass in gram (g):	
Lithium ion: Indicate watt-hour rating (Wh):	
Lithium metal: Indicate lithium metal content in gram (g):	
Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):	

7. Physical description of battery

lithium ion polymer pouch type battery

8. Model numbers

573230

TESTS AND RESULTS

9. List of tests conducted and results - Mark N/A, pass or fail with an "•"	N/A	pass	fail
T1 - Altitude simulation	\bigcirc	\bigcirc	0
T2 - Thermal Test	0	\bigcirc	0
T3 - Vibration	\bigcirc	\bigcirc	0
T4 - Shock	\bigcirc	\bigcirc	0
T5 - External Short Circuit	\bigcirc	\bigcirc	\bigcirc
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm See check point 1a and 9a.	0	$oldsymbol{O}$	0
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm. See check point 1a and 9a.	0	$oldsymbol{O}$	0
T7 - Overcharge	0	\bigcirc	0
T8 - Forced Discharge, only valid for cells. See check point 1a and 9a.	\bigcirc	\bigcirc	0
	\bigcirc	0	0
	0	0	0



Page 2

IN ACCORDANCE WITH SUB-SECTION 38.3

OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

Part no. 215617-01

9a.UN 38.3 Test Confirmation for the Cells inside the battery When no separate document for the cells is provided, this confirms that

the cells inside the battery (see checkpoint 1.a.) have successfully passed the UN 38.3 test. In this case under checkpoint 9 the T.6 and T.8 must be marked as "passed" and here under 9.a. "Cell UN 38.3 Test confirmed" needs to be ticked.

Cell UN 38.3 Test confirmed Cell UN 38.3 Test NOT confirmed

10. Reference to assembled battery testing requirements		
United Nations Recommendations on the Transport of Dangerous Goods, Manual of Tests & Criteria	N/A	

11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto

Revision 6, Amd. 1

ADDITIONAL SUPPLIER INQUIRY

12. Quality management system for manufacturing batteries Does the manufacturer of the battery manufacture the products based on a documented quality management system according to transport regulations?	YES	
13. Are the following parameters exceeded? Lithium ion battery: more than 100 Wh Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh	YES	
Check point 14 – 16 need to be answered when 13 has been ticked "YES":		
14. Does each battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?	YES	
15. Is each battery equipped with an effective means of preventing external short circuits?	VES	
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?	YES	NO

17. Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion batteries and lithium polymer batteries			
State of Charge (SoC) max. 30 %	N/A	YES	



Page 3

IN ACCORDANCE WITH SUB-SECTION 38.3

OF MANUAL OF TESTS AND CRITERIA

Name/Description of battery (taken from field 1)

Part no. 215617-01

BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the batteries are installed in articles:			
18.a) Only button cells enclosed?	YES		
18.b) Number of enclosed batteries per equipment		1	
When the equipment is intentionally active/switched on during transport e.g. data loggers:			
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment • N/A	YES		
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160	YES	NO	

19. Place, Date	20. Title, Surname, First name	21. Company stamp and signature
Santa Cruz, CA 15 January 2021	Staff Regulatory Compliance Engineer	Catherine Pell Digitally signed by Catherine Pell Date: 2021.01.15 12:32:58 -08'00'

