

Product Datasheet uvex 1 G2 6833 7 - 0 S2 SRC



UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	• ultra-lightweight S1 safety boot • made from synthetic materials, making it suitable for people allergic to chrome • all sole materials are free of silicone, plasticisers and other paint wetting impairment substances
Protection features	• new, innovative uvex i-PUREnrj sole technology with the highest level of shock-absorbing properties at the forefoot and at the heel, excellent rebound over the entire midsole and optimal stability thanks to the foam heel basket • meets the ESD specification with volume resistance under 35 megaohms • new wider 100% metal-free uvex xenova® safety toe cap for more toe room and optimum fit – compact design, anatomical shape, good lateral stability and no thermal conductivity
Comfort features	• outstanding wearer comfort thanks to a newly developed last and climate-optimised, breathable materials • virtually seam-free, perforated upper in high-tech microvelour to eliminate pressure points • removable antistatic comfortable insole with a moisture transport system, additional shock absorption around the heel and forefoot and excellent support for the arch • soft padding on the dust tongue and collar

	• sizes 35 to 40 have been produced using a women's last																								
Outsole	• PUR outsole, non-marking • ergonomically designed outsole incorporates the latest biomechanical research, consisting of two layers of uvex i-PUREnrj polyurethane with excellent slip resistance. The tread is particularly suited to industrial floor surfaces • excellent cushioning and extremely flexible • especially lightweight thanks to unique PUR sole unit • excellent slip resistance, self-cleaning tread • resistant to oil and petrol																								
Certificates	• Certified with uvex medicare for individual, orthopedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.																								
Areas of application	• light applications																								
Technical data	uvex 1 G2 boot S2 SRC <table><tr><td>Art.-no.</td><td>6833</td><td>7</td><td>8</td><td>9</td><td>0</td></tr><tr><td>Width</td><td></td><td>10</td><td>11</td><td>12</td><td>14</td></tr><tr><td>Standard</td><td colspan="5">EN ISO 20345:2011 S2 SRC</td></tr><tr><td>Size</td><td colspan="5">35 – 52</td></tr></table>	Art.-no.	6833	7	8	9	0	Width		10	11	12	14	Standard	EN ISO 20345:2011 S2 SRC					Size	35 – 52				
Art.-no.	6833	7	8	9	0																				
Width		10	11	12	14																				
Standard	EN ISO 20345:2011 S2 SRC																								
Size	35 – 52																								
Accessories	<i>Removable uvex 1 G2 comfortable climatic insole</i> (article no.: 94907 - 94900) • improved full-surface shock absorption • ultra-breathable, moisture-absorbing and quick-drying materials • shock absorption zones support natural movement of the foot • non-irritating, comfortable surface structure • anti-static properties • arch support <i>Laces</i> • black (article no.: 9599913)																								