

Tear Keyfob

– ATA5577

Colorful Tear Keyfob for Access Control

Tear Keyfob is made to serve your daily access control and security applications. This keyfob can be placed on a keyring or lanyard so people can carry it for multiple applications. We offer you 10 different color options while the white portion of the keyfob provides an excellent area for digital printing which brings out vivid color effect. You can customize your Tear Keyfob for your company identify or branding purpose.




Features

- 10 different color housing for selection
- Good ID numbering or logo marking

Applications

- Access Control
- System Login Verification

Physical Specification



Dimension


L	40	mm /	1.57	in
W	31	mm /	1.22	in
T	5	mm /	0.20	in

*The exact size is mainly based on metric unit.

Color	Red / Pink / Yellow / Green / Blue / Purple / White / Black / Orange / Grey
Material	ABS
Attachment	Key ring(*optional not include)
Options	Laser Marking/ Inkjet Printing/ UV Inkjet Printing

RF Specification

RFID Chip	Atmel ATA5577
Memory	User memory 363 bits
RF Interface Protocol	ISO/IEC 11784/11785
Operating Frequency	125 KHz
Applicable Surface	Non-metal



* LF sensitivity shown in the figure is measured by Testram Pro Loop Antenna 72phi. Actual sensitivity performance is subject to the environment in practice.

Environmental Resistance

Operating Temperature	-25°C to 55°C
Storage Temperature	-25°C to 75°C
Warranty	One Year
IP Rating	IP66

Ref. No:ST-011-P-113076-A

SAG All rights reserved. Product specifications may change without prior notice.

SAG reserves the right to alter specifications at any time without obligation to update previously supplied data. Our products are warranted against defects in material and workmanship under normal use. This warranty excludes accidental damage, wear and tear, misuse, improper handling, and unauthorized modifications. SAG is not liable for any indirect, incidental, consequential, or punitive damages, including loss or damage to devices, data, or records. Users must verify product suitability and compatibility for their applications. To minimize risks, follow all usage guidelines and safety instructions, particularly regarding electrostatic discharge (ESD).