## LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

N/A = Not Applicable

1.	Name/Description of cell
	BN 2542811, Li-ion 9V cell, Voltcraft

2. Manufacturer of cell		
Name	CEI Conrad Electronic International (HK) Limited	
Address	18 Flr, Tower 2, Nina Tower, No. 8 Yeung UK Road, Tsuen Wan, NT, HK	
Phone	(852) 2559 6328	
Email	hindratno.setiadharma@cei-hk.com	
Website	www.cei-hk.com	

2a. Manufacturer of the equipment (if the cell is contained in equipment)		
Name		
Address		
Phone		
Email		
Website		

3. Test laborat	3. Test laboratory of cell		
Name	Guangzhou Liya Battery Co., Ltd.		
Address	No. 383 Guangzhu Road, Dagang Town, Nansha, Guangzhou		
Phone	020-3498 0351		
Email sales01@gplibatt.com			
Website	www.gplibatt.com		

4. ID-number and date			
Unique test report identification number	GP20180606590932D-1	Date of test report	June 06, 2019

### **DESCRIPTION OF CELL**

5. Mark the type of cell with an "•"	
Lithium ion cell	Lithium metal cell



## LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of cell (taken from field 1)

BN 2542811, Li-ion 9V cell, Voltcr

6. Parameters	Cell	
Mass in gram (g):	35	
Lithium ion: Indicate watt-hour rating (Wh):		
Lithium metal: Indicate lithium metal content in gram (g):		
7. Physical description of cell		

	Li-ion cykindrical 9 V 500 mAh
8.	Model numbers
	LIR 9V

#### **TESTS AND RESULTS**

9. List of tests conducted and results - Mark N/A, pass or fail with an " "	N/A	pass	fail
T1 - Allitude simulation		0	
T2 - Thermal Test		•	
T3 - Vibration		•	
T4 - Shock		0	
T5 - External Short Circuit		0	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm		•	
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm	0	•	0
T7 - Overcharge		•	
T8 - Forced Discharge	Ó	0	Ó
	Ó	Ó	Ó

10. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto

United Nations Recommendation on the Transport of the Dangerous Goods, Manual of test and criteria (ST/SG/AC.10/11/Rev.6), Part III sub-section.



# LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of cell (taken from field 1)

BN 2542811, Li-ion 9V cell, Voltcr

#### ADDITIONAL SUPPLIER INQUIRY

Does the manufacture	system for manufacturing cells rof the cell/battery manufacture the products bas anagement system according to transport regula			
12. Are the following para Lithium ion cell: more Lithium metal cell: mo	than 20 Wh	YES NO		
Check point 13 – 15 need to	be answered when 12 has been ticked "YES":			
	rates a safety venting device or is designed upture under normal conditions of carriage?	YES NO		
14. Is each cell equipped v	vith an effective means of preventing external sho	ort circuits? YES NO		
15. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)				
16. Only in air transport: S	State of Charge (SoC) for UN 3480 Lithium ion	cells and lithium polymer cells		
State of Charge (SoC) r	max. 30 %	N/A YES NO		
CELLS INSTALLED IN				
17. Check point 17 needs	to be answered when the cells are installed in a	rticles:		
17.a) Only bulton cells en	closed?	YES NO (		
17.b) Number of enclosed cells (other than button cells) per equipment				
When the equipment is in	tentionally active/switched on during transport e	.g. data loggers:		
17.c) Confirmation that no dangerous amount of heat is emitted from the equipment N/A YES NO				
	equipment when transported by air fulfills the de s for electromagnetic radiation according to DO-16			
18. Place, Date	19. Title, Surname, First name	20. Company stamp and signature		
05 January 2024	QA Manager: Setjadharma, Hindratno	(MRH mahaha)		

