

VOLTCRAFT - RELIABLE AND PRECISE. SINCE 1982.

For decades, our product range has been dynamically adapting to the constant changes in the industry. We commit to offering first-class quality to our customers while delivering an excellent cost-performance ratio. This philosophy remains the cornerstone of Voltcraft's success.

UC-3ACX002 USB CHARGER (100 W)



Item no: 2582114

The product is a USB charger. The following charging ports are available:
2x USB-C™ (supports power delivery fast charge) //
1x USB-A (supports super quick charge)

TECHNICAL DATA

Data according to EU regulation 2019/1782

Manufacturer	Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau
Commercial registration number	HRB 3896
Model identifier	UC-3ACX002
Input voltage	100 - 240 V/AC
Input AC frequency	50 / 60 Hz
Output voltage	USB-C™ 1: 5.0 V/DC, max. 3.0 A, max. 15.0 W 9.0 V/DC, max. 3.0 A, max. 27.0 W 12.0 V/DC, max. 3.0 A, max. 36.0 W 15.0 V/DC, max. 3.0 A, max. 45.0 W 20.0 V/DC, max. 5.0 A, max. 100 W USB-C™ 2: 5.0 V/DC, max. 3.0 A, max. 15.0 W 9.0 V/DC, max. 3.0 A, max. 27.0 W 12.0 V/DC, max. 3.0 A, max. 36.0 W 15.0 V/DC, max. 3.0 A, max. 45.0 W 20.0 V/DC, max. 5.0 A, max. 100 W USB-A: 5.0 V/DC, max. 3.0 A, max. 15.0 W 5.0 V/DC, max. 4.5 A, max. 22.5 W 9.0 V/DC, max. 2.0 A, max. 18.0 W 12.0 V/DC, max. 1.5 A, max. 18.0 W Output USB-C™ 1 + USB-A: max. 65.0 W + max. 22.5 W
Output current	
Output power	



	Output USB-C™ 2 + USB-A: max. 65.0 W + max. 22.5 W Output USB-C™ 1 + USB-C™ 2: max. 65.0 W + max. 30.0 W Output USB-C™ 1 + USB-C™ 2 + USB-A: max. 45.0 W + max. 30.0 W + max. 22.5 W
Average active efficiency	85.0 %
Efficiency at low load (10 %)	71.0 %
No-load power consumption	0.28 W

Environment

Operating temperature	0 to +35 °C
Operating humidity	10 - 90 % RH (non-condensing)
Storage temperature	-20 to +70 °C
Storage humidity	10 - 90 % RH (non-condensing)

Others

Dimensions (L x W x H) (approx.)	106.3 x 68.6 x 33.8 mm
Weight (approx.)	220 g

CONTENTS

Product // USB-C™ to USB-C™ charging cable (2 m) // Operating instructions

This is a publication by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92242 Hirschau (www.conrad.com).

All rights including translation reserved. Reproduction by any method (e.g. photocopying, microfilming or the capture in electronic data processing systems) requires prior written approval from the editor. Reprinting, also in part, is prohibited. This publication reflects the technical status at the time of printing.

Copyright by Conrad Electronic SE.

*2582114_V1_0926_en_ds 3300603019 I1/O1 en