


Han Domino DD cube, crimp (F.2)



/	
Part number	09 14 906 2101
Specification	Han Domino DD cube, crimp (F.2)
HARTING eCatalogue	https://b2b.harting.com/09149062101

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Modules
Series	Han-Modular [®]
Type of module	Han [®] Domino DD Cube
Size of the module	Domino module
Description of the module	Large Tab
Version	
Termination method	Crimp termination
Gender	
Gender	Female
Number of contacts	Female 6

Technical characteristics

Conductor cross-section	0.14 2.5 mm²
Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Insulation resistance	>10 ¹⁰ Ω
Limiting temperature	-40 +125 °C
Mating cycles	≥500
Mating cycles with other HMC components	≥10,000

Page 1 / 2 | Creation date 2022-06-03 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
Specifications and approvals	
Specifications	EN 60664-1
opecinications	IEC 61984
Commercial data	
Packaging size	2
Net weight	0.01 kg
Country of origin	Romania
Country of origin European customs tariff number	Romania 85389099