


RAYCHEM | RAYCHEM VERSAFLEX

TE Internal #: A584924001 Heat Shrink Tubing, Black, Braid Wall, Polyester, Non-Flame-Retardant, Box, -50 – 150 °C, Resistant To Mechanical Damage, Flexible, RAYCHEM VERSAFLEX

View on TE.com >

Heat Shrink Tubing



Primary Product Color: Black Wall Type: Braid Primary Product Material: Polyester Heat Shrink Tubing Flammability: Non-Flame-Retardant Packaging Method: Box

Features

Product Type Features

Product Family

Wall Type

= 7Econnectivity

VERSAFLEX

Braid

Body Features

Primary Product Color	Black
Primary Product Material	Polyester
Flexibility	Flexible
Dimensions	
Heat Shrink Tubing Size Range	3 – 9 mm[.118 – .354 in]
Usage Conditions	
Fluid Resistance	Splash Protection
Heat Shrink Tubing Flammability	Non-Flame-Retardant
Operating Temperature Range	-50 – 150 °C
Heat Shrink Tubing Resistance	Mechanical Damage
Product Availability	
Applicable Region	Global
Packaging Features	
Packaging Method	Box

C For support call+1 800 522 6752

VERSAFLEX-05-0-SP

Heat Shrink Tubing, Black, Braid Wall, Polyester, Non-Flame-Retardant, Box, -50 – 150 °C, Resistant To Mechanical Damage, Flexible, RAYCHEM VERSAFLEX



Other

Meets Low Outgassing Requirements	No
Product Source	Europe
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Also in the Series RAYCHEM VERSAFLEX

& For support call+1 800 522 6752

VERSAFLEX-05-0-SP


Heat Shrink Tubing, Black, Braid Wall, Polyester, Non-Flame-Retardant, Box, -50 – 150 °C, Resistant To Mechanical Damage, Flexible, RAYCHEM VERSAFLEX





Customers Also Bought







TE Part #281934-2 SINGLE WIRE SEAL TE Part #0460-202-16141 DEUTSCH SOLID CONTACTS

Documents

Datasheets & Catalog Pages VERSAFLEX - Expandable Braided Polyester Sleeving English

Product Specifications Quality Specification

English