



PCB 480 V for 3RW55, Size 1, 13 A

Figure similar

product designation	Printed circuit board
design of the product	480 V, 13 A
manufacturer's article number	
• of soft starter	<a href="#">3RW5513-HA.4</a>
Substance Prohibittance (Date)	02/15/2018

**Ambient conditions**

ambient temperature during storage	-40 ... +80 °C
------------------------------------	----------------

**Certificates/ approvals**

General Product Approval	For use in hazard-ous locations	Declaration of Conformity	Test Certificates
--------------------------	---------------------------------	---------------------------	-------------------

[Confirmation](#)



[Explosion Protection Certificate](#)



[Type Test Certificates/Test Report](#)

Marine / Shipping	other
-------------------	-------



[Confirmation](#)

**Further information**

Siemens has decided to exit the Russian market (see here).  
<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.  
 Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)  
<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5951-0PA04>

Cax online generator  
<https://support.automation.siemens.com/WWW/CAXorder/default.aspx?lang=en&mlfb=3RW5951-0PA04>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/3RW5951-0PA04>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5951-0PA04&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5951-0PA04&lang=en)

Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current  
<https://support.industry.siemens.com/cs/ww/en/ps/3RW5951-0PA04/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5951-0PA04&objecttype=14&gridview=view1>

**Simulation Tool for Soft Starters (STS)**

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

---

last modified:

1/18/2021 

