SIEMENS

Data sheet 3RW5953-0PY06

PCB 690 V for 3RW55, Size 2 and 3




Figure similar

General Product Approval	For use in hazard-	Declaration of Conformity	Test Certificates			
Certificates/ approvals						
ambient temperature during storage		-40 +80 °C				
Ambient conditions						
Substance Prohibitance (Date)		02/15/2018				
of soft starter		3RW552HA.6, 3RW553HA.6				
manufacturer's article number						
design of the product	690	690 V				
product designation	Prin	Printed circuit board				
	D :					

Confirmation



Explosion Protection
Certificate





Type Test Certificates/Test Report

Marine / Shipping









Confirmation

other

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5953-0PY06

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3RW5953-0PY06}$

 $Service \& Support \ (Manuals, \ Certificates, \ Characteristics, \ FAQs, ...)$

https://support.industry.siemens.com/cs/ww/en/ps/3RW5953-0PY06

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ EPLAN\ macros,\ ...)$

nttp://www.automation.siemens.com/bilddb/cax_de.aspx?mitb=3Rvv5953-UPY06&lang=en

 $\label{lem:characteristic:} Characteristics. I^2t, Let-through current $$ $$ \underline{https://support.industry.siemens.com/cs/ww/en/ps/3RW5953-0PY06/characteristics. I^2t, Let-through current $$ \underline{https://support.industry.siemens.com/cs/ww/en/ps/3RW5953-0PY06/characteristics. I^2t, Let-through current $$\underline{https://support.industry.siemens.com/cs/ww/en/ps/3RW5953-0PY06/characteristics.}$$

Characteristic: Installation altitude

	w.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5953-0PY06&objecttype=14&gridview=view1 on Tool for Soft Starters (STS) upport.industry.siemens.com/cs/ww/en/view/101494917						
t modified:		1/18/2021 🗗					