

Pin busbar, 1-phase 10 mm², 12 pins, Insulation gray can be cut, with end caps



Model		
product brand name	SENTRON	
product designation	Pin busbar	
design of the product	1PH 10 mm², 12 pins gy	
General technical data		
phase number	1	
cross-section	10 mm²	
Main circuit		
operational current rated value	63 A	
Product details		
product feature insulated	Yes	
Connections		
type of electrical connection	Pin	
Mechanical Design		
width	6.4 mm	
length	214 mm	
General Product Approval		Declaration of Conformity
		other

[Confirmation](#)

[Miscellaneous](#)



[Confirmation](#)

other	Environment
-------	-------------

[Miscellaneous](#)

[Environmental Con-
firmations](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3762>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3762>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3762

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



¹⁾ Pin spacings in MW (Modular widths, 1 MW = 18 mm).

