

SIMATIC CFU PA Bundle with aluminum enclosure Bundle consisting of: 1x SIMATIC CFU PA (6ES7655-5PX11-0XX0) 1x SIMATIC CFU push-in terminals (6ES7655-5PX00-1XX0) 1x aluminum enclosure with: Cable glands Shield busbar Shield terminals Pre-mounted and checked



Figure similar

General information	
Product type designation	PA Bundle
Firmware version	
• FW update possible	Yes
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	060DH
Number of channels	16
Product function	
• I&M data	Yes; I&M0 to I&M4
• Isochronous mode	No
• The user can configure digital channels as input/output as required	Yes
• Digital channels can be parameterized	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V17
• STEP 7 configurable/integrated from version	V5.6 HF2 and higher
• PCS 7 configurable/integrated from version	V9.0 SP2 and higher
• PCS neo can be configured/integrated from version	V3.0
• PROFIBUS from GSD version/GSD revision	- / -
• PROFINET from GSD version/GSD revision	GSDML V2.3
Operating mode	
• Counter	Yes
Installation type/mounting	
Mounting position	Horizontal, vertical
Recommended mounting position	horizontal set up
Supply voltage	
Type of supply voltage	24 V DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Redundant power supply	Yes
Mains buffering	
• Mains/voltage failure stored energy time	5 ms; Bridging for field devices and communication
Input current	
Current consumption (rated value)	2.5 A
Current consumption, max.	2.55 A
Inrush current, max.	8 A

I ² t	0.3 A ² ·s
Encoder supply	
Number of outputs	8
Output voltage, min.	18.2 V
Short-circuit protection	Yes; Electronic
Output current	
• up to 60 °C, max.	2 A
• up to 70 °C, max.	1 A
Power loss	
Power loss, typ.	8.2 W; Depending on the type of BusAdapter used (typ. RJ45)
Address area	
Address space per station	
• Address space per station, max.	1 440 byte; Dependent on configuration
Digital inputs	
Number of digital inputs	8
Source/sink input	Yes; P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input characteristic curve in accordance with IEC 61131, type 2	No
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Pulse extension	No
Number of simultaneously controllable inputs	
horizontal installation	
— up to 60 °C, max.	8; Total current must be observed, see DQ
— up to 70 °C, max.	8; Total current must be observed, see DQ
vertical installation	
— up to 60 °C, max.	8; Total current must be observed, see DQ
Digital input functions, parameterizable	
• Counter	Yes
— Number, max.	1
— Counting frequency, max.	1 kHz
— Counting width	32 bit
— Counting direction up/down	Yes; Up
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	+11 to +30V
Input current	
• for signal "1", typ.	2.5 mA; Typical
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", max.	3.2 ms; for counter function 0,1 ms
— at "1" to "0", max.	3.2 ms; for counter function 0,1 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	8
Current-sinking	No
Current-sourcing	Yes
Short-circuit protection	Yes
• Response threshold, typ.	0.7 to 1.3 A
Limitation of inductive shutdown voltage to	Typ. L+ (-50 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	12 kΩ

Output voltage	
<ul style="list-style-type: none"> Type of output voltage for signal "1", min. 	DC Ue minus 1 V
Output current	
<ul style="list-style-type: none"> for signal "1" rated value for signal "0" residual current, max. 	0.5 A 0.1 mA
Output delay with resistive load	
<ul style="list-style-type: none"> "0" to "1", max. "1" to "0", max. 	50 µs 100 µs
Parallel switching of two outputs	
<ul style="list-style-type: none"> for uprating for redundant control of a load 	No No
Switching frequency	
<ul style="list-style-type: none"> with resistive load, max. with inductive load, max. on lamp load, max. 	100 Hz 2 Hz 10 Hz
Total current of the outputs	
<ul style="list-style-type: none"> Current per channel, max. 	0.5 A
Cable length	
<ul style="list-style-type: none"> shielded, max. unshielded, max. 	1 000 m 600 m
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> 2-wire sensor — permissible quiescent current (2-wire sensor), max. 	Yes 1.5 mA
Interfaces	
Number of PROFINET interfaces	1
Number of PROFIBUS interfaces	0
PROFIBUS PA	
<ul style="list-style-type: none"> Transmission rate, max. Number of connectable PA field devices Current output to PA field devices, max. permissible current per spur line Automatic addressing System-supported integration of field devices via PA profiles Extended fieldbus diagnostics 	31.25 kbit/s 8; electrically isolated from other interfaces, isolation tested at 2 500 V DC 320 mA 40 mA Yes Yes Yes
1. Interface	
Interface type	PROFINET
Isolated	Yes
Interface types	
<ul style="list-style-type: none"> Number of ports integrated switch BusAdapter (PROFINET) 	2 Yes Yes
Protocols	
<ul style="list-style-type: none"> PROFINET IO Device PROFIBUS DP slave 	Yes No
Interface types	
RJ 45 (Ethernet)	
<ul style="list-style-type: none"> 100 Mbps Autonegotiation Autocrossing 	Yes Yes Yes
Protocols	
Supports protocol for PROFINET IO	Yes
Redundancy mode	
<ul style="list-style-type: none"> PROFINET system redundancy (S2) 	Yes; Type S2
Media redundancy	
<ul style="list-style-type: none"> — MRP 	Yes
Open IE communication	
<ul style="list-style-type: none"> LLDP 	Yes
Interrupts/diagnostics/status information	

Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes
Diagnoses	
• Monitoring of encoder power supply	Yes
• Wire-break	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes
• Status indicator digital input (green)	Yes
• Status indicator digital output (green)	Yes
• Spur line status/fault	Yes
Potential separation	
between the channels and PROFINET	Yes
Potential separation digital inputs	
• between the channels	No
• between the channels and the power supply of the electronics	No
Potential separation digital outputs	
• between the channels	No
• between the channels and the power supply of the electronics	No
Isolation	
Isolation tested with	1 500 V AC between PROFINET and electronics
Degree and class of protection	
IP degree of protection	IP66
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-40 °C
• horizontal installation, max.	60 °C; max. 1 A load current; 50 °C to max. 2 A load current
• vertical installation, min.	-40 °C
• vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Relative humidity	
• Operation, max.	95 %
connection method	
Design of electrical connection	Connection plug
connection method / spur line / header	
• number of connections / for PROFIBUS PA spur line	8
• design of the PROFIBUS PA spur line	Type A
• diameter / of the PROFIBUS PA spur line / connectable / minimum	6 mm
• diameter / of the PROFIBUS PA spur line / connectable / maximum	12 mm
• connectable conductor cross-section / of the PROFIBUS PA spur line / minimum	0.2 mm ²
• connectable conductor cross-section / of the PROFIBUS PA spur line / maximum	2.5 mm ²
• Cable length, max.	120 m
• output current / for PROFIBUS PA spur lines / total / maximum	320 mA
• number of PROFIBUS PA field devices / connectable	8
• output current / per PROFIBUS PA spur line / maximum	40 mA
• No-load voltage, max.	15.3 V
• product feature / of the PROFIBUS PA spur line / short-circuit proof	Yes
• short-circuit current / of the PROFIBUS PA spur line / as test current / maximum	8 mA

- product feature / of the connections for PROFIBUS PA spur line / intrinsically safe according to FISCO model
- product function / of the connections for PROFIBUS PA spur line / debounce logic

Yes
Yes

Dimensions	
------------	--

Width	414 mm
Height	266 mm
Depth	111 mm

Weights	
---------	--

Weight, approx.	5.5 kg
-----------------	--------

last modified: 4/1/2022 