

USB keyboard INT, TKL-105, Cable with connector type A Desktop keyboard for devices with corresponding interface Color: black Further information, Quantity and content: see technical data



General information	
Product type designation	USB keyboard international US
Control elements	
Version of actuating element	Long-stroke key with 4 mm contact travel
Operating principle of the actuating element	Keyboard with long-stroke keys with membrane switching contacts
Input device	
• Scroll wheel	No
• Movement tracking	none
Keyboard fonts	
• Design	Keyboard with long-stroke keys
• Keyboard assignment	105 keys, international US layout
• Color of the buttons	Black
• Color of the key inscription	White
• Key illumination	No
• Function keys	Yes
— Number of function keys	12
— Number of function keys with LEDs	0
— Programmable	No
• Number pad	Yes; Free-standing
• status LED displays	Yes; Num, Caps and Scroll
— for number pad	Yes
— for Shift keys	Yes
Connection type	
• USB	Yes; USB 2.0 type A
• PS/2	No
• Cable length	0 m; See cable length
Frame size/design	
• Standard	Yes; For industrial applications
Installation type/mounting	
Mounting	Desktop
Mounting type	none
Supply voltage	
Rated value (DC)	5 V; via USB
Battery	
Battery-operated	No; maintenance-free
Interfaces	
Number of USB interfaces	1; USB 2.0
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes; Compliance with EN 55032 Class B limit values; interference emission:

Degree and class of protection

IP (all-round)	IP68 all-round and dishwasher safe
IP (at the front)	USB connector without degree of protection

Standards, approvals, certificates

CE mark	Yes
UL approval	Yes; cUL
cULus	Yes; cUL
KC approval	Yes
EAC (formerly Gost-R)	Yes
BIS	No; required for export to India
RoHS conformity	Yes
Suitable for safety functions	No

Ambient conditions

Suited for indoor use	Yes
Suited for outdoor use	No; possible under certain conditions

Ambient temperature during operation

• min.	0 °C
• max.	70 °C

Ambient temperature during storage/transportation

• min.	-20 °C
• max.	60 °C

Relative humidity

• Operation, max.	80 %; no condensation
• Condensation permissible	No

Operating systems

Runs under operating system	
• Windows CE	Yes
• Windows Vista	Yes
• Windows XP	Yes
• Windows 7	Yes
• Windows 8	Yes
• Windows 10	Yes

Cables

Cable length	1.5 m; USB
--------------	------------

Mechanics/material

Material	
• Plastic	Yes; Black
Enclosure material (front)	
• Plastic	Yes; ABS with antimicrobial coating
Enclosure color (front)	Black
Enclosure color (rear)	Black

Torques/forces

• Breakdown torque	0.53 N·m; Switching force buttons
--------------------	-----------------------------------

Service life

• Number of operating cycles, keys	10 000 000; Operations (minimum)
------------------------------------	----------------------------------

Dimensions

Width	459 mm
Height	35 mm
Depth	174 mm

Weights

Weight (without packaging)	800 g
Weight (with packaging)	1 620 g

Scope of supply

Delivery quantity in pieces	1
-----------------------------	---

Other

printable with laser printer	No
Merchandise	Yes; GETT TKL-105
Manufacturer name	GETT Gerätetechnik GmbH

Manufacturer's address	Mittlerer Ring 1, 08233 Treuen (Vogtland), Germany
contacting the manufacturer	Phone +49 37468 660-0, email: info@gett.de
Target devices	For SIMATIC HMI devices and IPCs with the appropriate slot
Note:	Corresponds to KL24603
Usable in the following products	
• Product 1	6AV2124-*
• Product 2	6AV2125-*
• Product 3	6AV2145-*
• Product 4	6AV7880-*
• Product 5	6AV7863-3MA00-0AA0
• Product 6	6AV7863-3MA00-0SA0
• Product 7	6AV7863-3MA20-0AA0
• Product 8	6AV7863-3TA00-0AA0
• Product 9	6AV7250-*
• Product 10	6AV7251-*
• Product 11	6AV7863*
• Product 12	6AV2128-3*
• Product 13	6AV6642-0BD01-3AX0
• Product 14	6AV6642-0BC01-1AX1
• Product 15	6AV6642-0DC01-1AX0
• Product 16	6AV6642-0DA01-1AX0
• Product 17	6AV6642-0EA01-3AX0
• Product 18	6AV6545-0CC10-0AX0
• Product 19	6AV6545-0AH10-0AX*
• Product 20	6AV6545-0DA10-0AX0
• Product 21	6AV6545-0DB10-0AX0
• Product 22	6AV6644-*
• Product 23	6AV6643-*
• Product 24	6AV2123-2*
• Product 25	6AV7862-2BC*
• Product 26	6AV7862-2BD*
• Product 27	6AV7862-2BE*
• Product 28	6AV7862-2BF*

last modified:

4/21/2021 