

touch pen caps RES, replacement caps for touch pen system for resistive touch screens more information, quantity and content: see technical specifications



Figure similar

General information	
Product type designation	Touch pen caps
Control elements	
Frame size/design	
• Standard	Yes; special cap only for resistive touch systems
Installation type/mounting	
Wall mounting/direct mounting	Yes; can be used for touch pen system ELO and V2A
Standards, approvals, certificates	
CE mark	No; No CE marking obligation
RoHS conformity	Yes; FDA§177.2600 compliant
FDA-compliant	Yes; FDA§177.2600 compliant
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	Yes; only suitable under certain conditions due to different environmental conditions; replacement cycle can be increased
Ambient temperature during operation	
• min.	-40 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended
• max.	80 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	80 °C
Relative humidity	
• Operation, max.	95 %
Accessories	
belongs to product	can be used for touch pen system ELO and V2A
Mechanics/material	
Material	
• Plastic	Yes; special cap only for resistive touch systems
Color	light beige
Torques/forces	
• Tightening torque, max.	Hand-tight
Dimensions	
Height	8 mm
Diameter	8 mm
Weights	
Weight (without packaging)	0.8 g
Weight (with packaging)	1.7 g

Scope of supply	
Delivery quantity in pieces	5; Caps for touch pen
Other	
Merchandise	Yes; touch replacement cap RES
Manufacturer name	QUERUM products UG
Manufacturer's address	Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany
contacting the manufacturer	email: querumproducts@web.de
Target devices	For common capacitive and resistive touch systems
Note:	food safe, suitable for F&B
Usable in the following products	
<ul style="list-style-type: none"> <li>• Product 1</li> <li>• Product 2</li> </ul>	<a href="#">6AV6881-0AV21-0AA0</a> <a href="#">6AV6881-0AV22-0AA0</a>

**last modified:** 6/13/2023 