

product type designation

product description

Antenna cable for HF, M8 / M8

Highly flexible coaxial cable

SIMATIC RF200/RF300 antenna connection cable PUR, UL 758, length 0.6 m trailing plug M8 straight/M8 angled to be connected between reader and antenna.



suitability for use

plug-in cable for connecting a short-range HF antenna ANT 12, 18 to a reader via M8 plug

cable designation

2YCC11Y 0.9/2.85 LI VZN BK

wire length

0.6 m

electrical data

number of electrical connections

2

type of electrical connection

M8 (male, 4 pin, straight) / M8 (male, 4 pin, angled)

impedance

- rated value

50 Ω

loop resistance per length / maximum

74 mΩ/m

operating voltage

- maximum

300 V

mechanical data

design of the shield

Braided shield made of tin-plated copper wires

outer diameter

- of cable sheath

5.6 mm

material

- of dielectric
- of cable sheath

PE

PUR

color

- of cable sheath

Black

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible
- with continuous bending

22.4 mm

44.8 mm

75 mm

number of bending cycles

3000000

weight per length

51 kg/km

ambient conditions

ambient temperature

- during operation
- during storage
- during transport
- during installation

-40 ... +80 °C

-40 ... +80 °C

-40 ... +80 °C

-40 ... +80 °C

fire behavior

flame resistant according to IEC 60332-1-2

radiological resistance / to UV radiation

resistant

product features, product functions, product components / general

product feature

- halogen-free

Yes

<ul style="list-style-type: none"> silicon-free 	Yes
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	Yes; UL style 1581, Sec. 1090 (H)
reference code	
<ul style="list-style-type: none"> according to IEC 81346-2 	WG
<ul style="list-style-type: none"> according to IEC 81346-2:2019 	WGB
further information / internet links	
internet link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool 	https://support.industry.siemens.com/cs/ww/en/view/67384964
<ul style="list-style-type: none"> to website: Industrial communication 	http://www.siemens.com/ident/rfid
<ul style="list-style-type: none"> to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> to website: CAx-Download-Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> to website: Industry Online Support 	https://support.industry.siemens.com

last modified:

5/28/2023 