



SITOP BAT1600/BATT.MODUL/24V/7.5AH

SITOP BAT1600 24 V DC 7.5 Ah LiFePO4 lithium battery for SITOP UPS1600 \*\*\*  
not for air freight \*\*\*

Charging current charging voltage	
end-of-charge voltage at DC	
<ul style="list-style-type: none"> <li>at -10 °C recommended</li> <li>at 0 °C recommended</li> <li>at 10 °C recommended</li> <li>at 20 °C recommended</li> <li>at 30 °C recommended</li> <li>at 40 °C recommended</li> <li>at 50 °C recommended</li> </ul>	28.8 V 28.8 V 28.8 V 28.8 V 28.8 V 28.8 V 28.8 V
Output	
output current rated value	40 A
charging current maximum	3 A
output voltage at DC rated value	24 V
Safety	
display version for normal operation	Three-color: green = Buffer ready; yellow = Buffer endangered; red = Buffer not possible
Safety	
operating resource protection class	Class III
protection class IP	IP20
Approvals	
certificate of suitability	
<ul style="list-style-type: none"> <li>CE marking</li> <li>UL approval</li> <li>as approval for USA</li> <li>CSA approval</li> <li>cCSAus, Class 1, Division 2</li> <li>ATEX</li> </ul>	Yes Yes UL-Listed (UL 621010, CSA C22.2 No. 107.1) No No No
certificate of suitability	
<ul style="list-style-type: none"> <li>C-Tick</li> <li>shipbuilding approval</li> </ul>	Yes Yes
shipbuilding approval	ABS, DNV GL
Marine classification association	
<ul style="list-style-type: none"> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> <li>DNV GL</li> </ul>	Yes Yes
environmental conditions	
Operating data note	For storage, mounting and operation of batteries, the relevant DIN/VDE regulations or country-specific regulations (e.g. VDE 0510 Part 2/EN 50272-2) must be observed.
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during transport</li> </ul>	-10 ... +50 °C -30 ... +70 °C

<ul style="list-style-type: none"> <li>during storage</li> </ul>	-20 ... +35 °C
relative temporary capacity loss at 20 °C in a month typical	1 %
<b>Service life</b>	
service life of energy storage	capacity falls to 80 % of original capacity (according to EUROBAT)
<ul style="list-style-type: none"> <li>typical</li> </ul>	11 a
<ul style="list-style-type: none"> <li>at 20 °C typical</li> </ul>	11 a
<ul style="list-style-type: none"> <li>at 30 °C typical</li> </ul>	8 a
<ul style="list-style-type: none"> <li>at 40 °C typical</li> </ul>	6 a
<ul style="list-style-type: none"> <li>at 50 °C typical</li> </ul>	2 a
<ul style="list-style-type: none"> <li>at 60 °C typical</li> </ul>	
ambient temperature during storage	Along with the storage and operating temperature, other factors such as the duration of the storage period and the charge status during storage have a decisive influence on the possible useful life. Batteries should therefore be stored as briefly as possible, always fully charged, and within the temperature range 0 to +20 °C.
<b>Mechanics</b>	
type of electrical connection	screw-type terminals
<ul style="list-style-type: none"> <li>for power supply unit</li> </ul>	1 screw terminal each for 0.5 ... 16 mm <sup>2</sup> for + BAT and - BAT
<ul style="list-style-type: none"> <li>for control circuit and status message</li> </ul>	1 screw terminal each for 0.2 ... 2.5 mm <sup>2</sup>
product component included	2x Maxi Fuse 50 A/32 V
width of the enclosure	238 mm
height of the enclosure	156 mm
depth of the enclosure	129 mm
installation width	238 mm
mounting height	256 mm
required spacing	
<ul style="list-style-type: none"> <li>top</li> </ul>	50 mm
<ul style="list-style-type: none"> <li>bottom</li> </ul>	50 mm
<ul style="list-style-type: none"> <li>left</li> </ul>	0 mm
<ul style="list-style-type: none"> <li>right</li> </ul>	0 mm
fastening method	
<ul style="list-style-type: none"> <li>wall mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>standard rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>S7 rail mounting</li> </ul>	Yes
fastening method	snaps onto DIN rail EN 60715 35x15 or wall mounting with accessories wall mounting set 6EP4990-0MK00-0XU0
net weight	4 kg
number of cells	3
battery capacity	7.5 A·h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

