

product type designation



Transponder RF1100T configuration

SIMATIC RF1000, Transponder RF1100T for the configuration of all RF1000 reader; MIFARE DESFire EV2 IP67, -25 ... +60°C, 85x 54x 0.8 mm Minimum order quantity 5;

suitability for operation

to copy a previously created configuration on RF1000 reader

radio frequencies

operating frequency / rated value	13.56 MHz
range / maximum	50 mm; Range depends on reader
protocol / with radio transmission	ISO 14443-A
transfer rate / with radio transmission / maximum	106 kbit/s
product feature / multitag-capable	No

electrical data

product component / backup battery	No
------------------------------------	----

memory

type of memory	EEPROM
storage capacity / of the user memory	8000 byte
type of memory organization	UID (fixed code) 7 bytes, user memory 8000 bytes (encrypted, configuration can only be created with special tool)
number of read cycles / at ambient temperature < 40 °C / maximum	1E+14
number of write cycles / at ambient temperature < 40 °C / maximum	1000000
data retention time / at ambient temperature < 40 °C / not less than	10 a
type of transponder chip used	MIFARE DESFire EV2

mechanical data

material	PVC
color	white
mounting distance / relating to metal surfaces / recommended / minimum	20 mm

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during read/write access outside the read/write area during storage 	-25 ... +60 °C -25 ... +60 °C -25 ... +60 °C
protection class IP	IP67

design, dimensions and weights

width	54 mm
height	0.8 mm
depth	86 mm
net weight	6 g

product features, product functions, product components / general

product feature	
<ul style="list-style-type: none"> printable 	Yes

printing process	handwriting with pen
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • IECEX 	No
further information / internet links	
internet link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/67384964 http://www.siemens.com/ident/rfid https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified:

2/10/2022 