

## Material Safety Data Sheet

---

### 1. Identification of the substance/mixture and of the company/undertaking

<b>Product name:</b>	Li-Ion battery, rechargeable
----------------------	------------------------------

Item No.	Nominal Voltage	Capacity	Energy content
2891367	3.7 V	20000 mAh	74 Wh

<b>Manufacturer:</b>	Conrad Electronic SE
<b>Address:</b>	Klaus-Conrad-Str. 1, D-92240 Hirschau
<b>Telephone:</b>	+49 (0) 9604 / 40 - 8988
<b>Date of issue:</b>	15.08.2023

### 2. Hazards Identification

#### Hazard Description

Not dangerous with normal use. Do not dismantle, open or shred the battery ingredients contained within or their ingredients products could be harmful.

#### Primary Route(s) of Exposure

Inhalation, Ingestion, Skin contact and Eye contact.

#### Potential Health Effects

##### Inhalation:

Vapors or mists from a ruptured battery may cause respiratory irritation.

##### Ingestion:

The battery ingredients contained within or their ingredients products can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.

##### Skin:

Skin contact with contents of an open battery can cause severe irritation or burns to the skin.

##### Eye:

Eye contact with contents of an open battery can cause severe irritation or burns to the eye.

## Material Safety Data Sheet

---

### 3. Composition/Information on Ingredients

Chemical Name	Concentration or concentration ranges (%)	CAS Number
Lithium Cobalt Oxide	35-38	12190-79-3
Graphite	20-22	7782-42-5
Copper	9-10	7440-50-8
Aluminum	5-6	7429-90-5
Ethylene carbonate	14-16	96-49-1
Polypropylene	5-6	9003-07-0
Carbonate, methyl ethyl	4-5	623-53-0
Phosphate(1-), hexafluoro-, lithium	5-6	21324-40-3

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

### 4. First Aid Measures

#### Inhalation

Remove source of contamination or move victim to fresh air. Obtain medical advice.

#### Ingestion

Please rinse mouth thoroughly with water. Induce vomiting under the guidance of professional personage. Please seek medical treatment in time.

#### Skin contact

Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.

#### Eye contact

Irrigate with flowing water for 15 minutes. If irritation persists, consult a physician.

### 5. Fire Fighting Measures

#### Characteristics of Hazard

Toxic fumes, gases or vapors may evolve on burning.

#### Hazardous Combustion Products

Carbon monoxide, carbon dioxide, lithium oxide fumes and so on.

#### Fire-extinguishing Methods and Extinguishing Media

Please use water, dry sand and other proper fire extinguishing media.

#### Attention in Fire-extinguishing

The firemen should put on antigas masks and full fire-fighting suits.

## Material Safety Data Sheet

---

### 6. Accidental Release Measures

#### Personal Precautions, protective equipment, and emergency procedures

Restrict access to area until completion of clean-up. Do not touch the spilled material. Wear adequate personal protective equipment as indicated in Section 8.

#### Environmental Precautions

Prevent material from contaminating soil and from entering sewers or waterways.

#### Methods and materials for Containment

Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.

#### Methods and materials for cleaning up

Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

### 7. Handling and Storage

#### Handling

Don't handling the batteries in manner that allows terminals to short circuit. Do not open, disassemble, crush or burn battery.

#### Storage

If the battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the battery periodically.

Long period more than 1 month:  $-10^{\circ}\text{C} \sim 35^{\circ}\text{C}$ ,  $65 \pm 20\% \text{R.H.}$

Do not storage the battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.

Keep out of reach of children.

Do not expose the battery to heat or fire. Avoid storage in direct sunlight.

Do not store together with oxidizing and acidic materials.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

No engineering controls are required for handling batteries that have not been damaged. Personal protective equipments for damaged batteries should include chemical resistant gloves and safety glasses.

#### Personal Protective Equipment

Respiratory Protection: In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use. Not necessary under conditions of normal use.

Protective Gloves: Not necessary under conditions of normal use.

Other Protective Clothing or Equipment: Not necessary under conditions of normal use.

Personal Protection is recommended for venting battery: Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

## Material Safety Data Sheet

---

### 9. Physical and Chemical Properties

#### Physical State

Form:	Solid
Color:	Black
Odour:	Odorless

#### Change in condition

pH, with indication of the concentration	No data is available
Melting point/freezing point	No data is available
Boiling Point, initial boiling point	No data is available
Flash Point	No data is available
Upper/lower flammability or explosive limits	No data is available
Vapor Pressure	No data is available
Vapor Density: (Air = 1)	No data is available
Density/relative density	No data is available
Solubility in Water	Insoluble
n-octanol/water partition coefficient	No data is available
Auto-ignition temperature	No data is available
Decomposition temperature	No data is available
Odour threshold	No data is available
Evaporation rate	No data is available
Flammability (soil, gas)	No data is available
Viscosity	No data is available

### 10. Stability and Reactivity

#### Stability

Stable under normal temperatures and pressures.

#### Conditions to Avoid

Heat above 70°C or Incinerate, Deform, Mutilate, Crush,  
Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions.

#### Hazardous Decomposition Products

Toxic Fumes, and may form peroxides.

#### Possibility of Hazardous Reaction

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalis, halogenated hydrocarbons.

## Material Safety Data Sheet

---

### 11. Toxicological Information

#### Irritation

In the event of exposure to internal contents, vapor fumes may be very irritating to the eyes and skin.

#### Sensitization

No data is available

#### Reproductive Toxicity

No data is available

#### Toxicologically Synergistic Materials

No data is available

### 12. Ecological Information

#### General note

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### Anticipated behavior of a chemical product in environment/possible environmental impact/ecotoxicity

No data is available

#### Mobility in soil

No data is available

#### Persistence and Degradability

No data is available

### 13. Disposal Considerations

#### Waste Treatment

Recycle or dispose of in accordance with government, state & local regulations.

#### Attention for Waste Treatment

Deserted batteries couldn't be treated as ordinary trash. Couldn't be thrown into fire or placed in high temperature. Couldn't be dissected, pierced, crushed or treated similarly. Best way is recycling.

## Material Safety Data Sheet

---

### 14. Transport Information

The 20000mAh Solar Power Bank (model: WT-S020) tested according to the requirements of the UNITED NATIONS "Manual of Tests and Criteria" Part III, subsection 38.3;

The 20000mAh Solar Power Bank was protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to short circuit;

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking.

The package must be handled with care and that a flammability hazard exists if the package is damaged.

With regard to transport, the following regulations are cited and considered:

#### **The International Air transport Association (IATA) Dangerous Goods Regulations**

The 20000mAh Solar Power Bank can be shipped by air in according to Section IB of PACKING INSTRUCTION 965 of the 2023 IATA Dangerous Goods regulations 64th Edition.

UN number of lithium battery: UN3480

UN Proper shipping name/Description (technical name): Lithium ion batteries

UN Classification (Transport hazard class): Class 9

PG Packing Group: N/A

#### **The International Maritime Dangerous Goods (IMDG) Code**

The battery is not restricted according to IMO IMDG Code (inc Amdt 40-20).

UN number of lithium battery: UN3480

UN Proper shipping name/Description (technical name): Lithium ion batteries

UN Classification (Transport hazard class): N/A

PG Packing Group: N/A

Marine pollutant(Y/N): N

Need to meet the Special Provision: International maritime dangerous goods code (IMDG) 188, 230, 348, 384.

EmS No.: F-A, S-I

## Material Safety Data Sheet

---

### 15. Regulatory Information

《Dangerous Goods Regulations》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods 》

《Occupational Safety and Health Act 》 (OSHA)

《Toxic Substance Control Act》 (TSCA)

《Consumer Product Safety Act 》 (CPSA)

《Federal Environmental Pollution Control Act》 (FEPCA)

《The Oil Pollution Act》 (OPA)

《Superfund Amendments and Reauthorization Act Title III (302/311/312/313)》 (SARA)

《Resource Conservation and Recovery Act》 (RCRA)

《Safety Drinking Water Act》 (CWA)

《California Proposition 65》

《Code of Federal Regulations》 (CFR) 49 CFR sections 100-185, 49 CFR -173.185

EU Battery Directive (2006/66/EC, 2013/56/EU)

Regulation (EC) No. 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH)

In accordance with all Federal, State and local laws.

### 16. Additional Information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.