

Part Number: 2196711101

Product Description: Pre-Crimped Lead Mini-Fit Sigma Female-to-Pigtail, Tin (Sn) Plating, 75.00mm Length, 20 AWG, Black

Series Number: 219671

Status: Active

Product Category: Power and Signal Cable

Assemblies



Documents & Resources

Drawings

Drawing 2196711101_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|------------------------|--|
| Category | Power and Signal Cable Assemblies |
| Series | 219671 |
| Description | Pre-Crimped Lead Mini-Fit Sigma Female-to-Pigtail, Tin (Sn) Plating, 75.00mm Length, 20 AWG, Black |
| Application | Power, Wire-to-Board, Wire-to-Wire |
| Assembly Configuration | Pre-crimped Lead Only |
| Connector to Connector | Mini-Fit Sigma-to-Pigtail |
| Product Family | Off-the-Shelf Pre-Crimped Leads |
| Product Name | Mini-Fit Sigma |
| UPC | 195842810983 |

Electrical

| Current - Maximum per Contact | 11.5A |
|-------------------------------|------------|
| Voltage - Maximum | 600V AC/DC |

Physical

| | 75.00 |
|--------------------------------|----------------------|
| Cable Length | 75.00mm |
| Circuits (Loaded) | 1 |
| Circuits (maximum) | 1 |
| Color - Resin | Black |
| Gender | Female-Pigtail |
| Material - Metal | Brass |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Net Weight | 0.699/g |
| Number of Rows | 1 |
| Packaging Type | Bag |
| Plating min - Mating | 2.500µm |
| Single Ended | Yes |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type | UL 11028 |

| Wire Insulation Diameter | 1.98-2.55mm |
|--------------------------|-------------|
| Wire Size (AWG) | 20 |

Use with Part(s)

| Description | Part Number |
|--|---------------|
| Mini-Fit TPA2 and Mini-Fit Sigma Dual Row Receptacle Housings | <u>172708</u> |
| Mini-Fit TPA2 and Mini-Fit Sigma Single Row Receptacle Housings | 200453 |

This document was generated on Sep 26, 2023