



PRODUCT

Antistatic Wastin Bin

TECHNICAL DATASHEET

Manufactured from carbon infused polypropylene, the antistatic waste bin can be safely used in a static controlled area.

TECHNICAL SPECIFICATIONS

SPECIFICATION	RESULT
Material	Antistatic polypropylene (PP)
Volume Resistance	10^4 - 10^6 ohms
Decay Time	1000V/100V @ less than 1.0s
Tirbo Charging	Less than 100V
Colour	Black
Printing	silk-screen antistatic logo on the outside

PRODUCT CODE	DESCRIPTION	CAPACITY (L)	QUANTITY
091-0054	Antistatic Wastin Bin	14	Each

To request a quotation or for more information, please call **+44 (0)1473 836200**
email info@antistat.co.uk or visit www.antistat.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Antistat or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Antistat assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Antistat was aware of the possibility of such loss or damage arising) is excluded. © 2023 Antistat.