

Breathing Protection

02.03.2021

Product data sheet uvex silv-Air 2310 FFP3 NR D



Product information

.	D 21 CH 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
Product	 Particle-filtering cup shape mask with exhalation valve 		
features	Protection level FFP3		
	Soft material edges for more high wearing comfort		
	 4-point headband attachment allows an individual and secure 		
	fit		
	 Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask 		
	Flexible and adjustable nose clip		
	Compatible with uvex safety eyewear		
	Soft sealing lip guarantees a secure, comfortable sealed		
	position of the mask		
	Mask fulfils the requirements of the dolomite dust test (D)		
Materials	Headband: textile		
	Nose clip: aluminum		
	Headband clips: PP		
	Filter / mask: Melt Blown PP, Polyester		
	Sealing lip: PVC foam		
	Valve: ABS		
Weight	29 g		
Standard	EN 149:2001 + A1:2009		

Versions

Article number	Colour/Version	Retail unit
8762310	cup shape mask FFP3, white with valve	15 pcs. per box
8742310	cup shape mask FFP3, white with valve	3 pcs. per bag

Packaging sizes

Box	approx. 260 x 140 x 180 mm
Outer Carton	approx. 570 x 550 x 290 mm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance	Inhalation resistance	Exhalation resistance
	30l/min.	95I/min.	160I/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be	Woodworking, hard wood, chromium,	
used against solid, aqueous and non-	asbestos (short periods of work), stainless	
volatile liquid aerosols up to 30 times the	steel, lead, welding, dust that contain	
respective limit values.	beryllium, arsenic, cadmium or cobalt.	
	Medical waste disposal, fungal spores,	
	legionella bacteria, infections, viruses,	
	bacteria, enzyme, nanoparticles.	

^{*}Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth