



CRC CARB & EGR CLEANER

I. General Description

Powerful solvent blend to remove gum, carbon and sludge from carburettors, EGR, PCV and throttle valves in combustion engines.

2.Characteristics

- Quickly dissolves carburettor deposits, providing faster starting and smooth idling.
- Dissolves soot, gum, carbon and oil deposits.
- None chlorinated solvents.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO₂ propellant, giving an active product content of 95%.

3.Applications

- Carburettor components.
- Positive Crankcase Venting (PCV) systems and valves.
- Exhaust Gas Recycling (EGR) valves.
- Throttle valve.

4.Instructions

Valve cleaning:

- Dismount and wet the contaminated surfaces and allow to act for 5 min. Repeat if needed. Allow the EGR and PCV valve to dry before re-assembling. Start engine at idle. Spray the throttle valve again and accelerate the engine with a couple of short impulses to 2000 rpm.

Carburettor cleaning:

- Stop engine and let it cool down. Remove air filter.
- Spray sparingly into carburettor, wetting all visible parts.
- Spray exterior surfaces until they are clean and allow to dry.
- Start engine. Whilst running at medium idle, spray directly into air intake. Accelerate.
- Stop engine. Lubricate and protect exterior parts and linkages with CRC 5-56.
- Put filter back into place and, if necessary, adjust air-fuel ratio

Note:

- If spilled or sprayed on painted surfaces, rubber or sensitive plastics, wipe or wash off immediately.
- Always follow the recommendations in the instruction manual provided by the equipment manufacturer.



Technical Data Sheet

CRC CARB & EGR CLEANER

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

5. TYPICAL PRODUCT DATA (without propellant)

• Appearance	:	Liquid.
• Color	:	Colorless
• Odor	:	Aromatic
• Density	:	0.75 g/cm ³ (@ 20°C)
• Flash Point	:	< 0 °C (Closed Cup)
• Auto Ignition temperature	:	> 200 °C

6. PACKAGING

Aerosol: 12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Date: 09/03/2023