KERN OLM 171



The inverted metallurgical microscope for professional applications



Category	
Brand	Optics
Product categoriy	Microscope
Product group	Metallurgical microscope
Product family	OLM-1
Approval	
CE mark	\checkmark
Construction	
Dimension (W×D×H)	747×271×379 mm

()	
Optical system	Infinity
Tube type	Siedentopf
Tube type	Trinocular
Tube angle of inclination	30°
Nosepiece screw-in locations	5
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Contrasting methods	Bright field Polarisation
Light distribution	100:0
Interpupillary distance [Max]	76 mm
Interpupillary distance [Min]	48 mm

Ocular	
Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10 x
Ocular visual field	22 mm
Ocular diameter	30 mm

Focussing	
Fine drive minimum	0,002 mm
Torque regulation	✓
Field of view [Min]	0,44 mm
Field of view [Max]	4,4 mm
Focusing mechanism	coaxial coarse and fine drive
Illumination	
Illumination type incident light	Halogen
Illumination intensity incident light	50 W
Illuminance	Reflected light
Illumination dimmable	Incident light
Field diaphragm	1
Aperture diaphragm	✓
Filter possible	✓
Brand of light bulb	Philips
Power Supply	
Input voltage power supply / power [Max]	100 - 240 V
Input voltage device / power [Max]	100 - 240 V
Plug-in power supply type	Built-in power supply
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO
	AUS
Plug-in power supply / adapter for	UK
countries - optional	US
	СН
Environmental conditions	
Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C
Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	660×590×325 mm
Net weight	12,968 kg
Shipping method	Parcel service
Net weight approx.	13 kg
Gross weight approx.	17 kg
Shipping weight	25,3 kg

KERN OLM 171



The inverted metallurgical microscope for professional applications

Objective

Pictograms

STANDARD

