KERN ORM 1AL



Digital measurement of refraction index for universal application



Category	
Brand	Optics
Product categoriy	Refractometer
Product group	Digital refractometer
Product family	ORM-AL

Measuring System			
Automatic temperature compensation (ATC)	✓		
Measuring method	Total reflection		
Area of application	Alcohol		
Percentage by volume	0-80%(v/v) @ 1%(v/v) ± 1%(v/v)		
Appropriate calibration liquid	0 % (distilled water)		
Measurement temperature [Min] (°C)	0 °C		
Measurement temperature [Max] (°C)	40 °C		
Brix scale	✓		
Readout Brix	0,1 %		
Measuring range Brix [Min]	0 %		
Measuring range Brix [Max]	50 %		
Accuracy Brix	±0,2 %		
Scale for Refractive index	✓		
Readout refractive index	0,0001 nD		
Measuring range refractive index [Min]	1,3330 nD		
Measuring range refractive index [Max]	1,4200 nD		
Accuracy refractive index	±0,0003 nD		
Scale percent by mass	✓		
Readout percent by mass	1 %		
Measuring range percent by mass [Min]	0 %		

Measuring range percent by mass [Max]	72 %
Accuracy percent by mass	±1 %
Scale volume percentage	✓
Readout volume percentage	1 %
Measuring range volume percentage [Min]	0 %
Measuring range volume percentage [Max]	80 %
Accuracy volume percentage	±1 %
Measuring range volume percentage [Max]	

Approval		
CE mark	✓	
0 1 1		

Construction	
Dimension (W×D×H)	121×58×25 mm
Refractometer type	Handheld refractometer
Scale - Display type	Digital

Functions	
Auto-off interval(s) in battery mode/rechargeable battery mode	60 sec
IP protection - complete device	IP65
Automatic temperature compensation	✓

Power Supply			
Supplied power supply	Battery		
Battery / accumulator type	Alkali(-Manganese)		
Battery connection	Pad + Spring		
Battery capacity	1.300 mAh		
Battery voltage	1,5 V		

Environmental conditions	
Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C
Packing & Shipping	

Packing & Shipping	
Dimensions transport container (W×D×H)	170×110×50 mm
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	170×110×50 mm
Net weight	0,14 kg
Shipping method	Parcel service
Net weight approx.	0,15 kg
Gross weight approx.	0,35 kg
Shipping weight	0,31 kg

1

KERN ORM 1AL



Digital measurement of refraction index for universal application

Services (optional)				
Article number for factory calibration			ictory	961-290
Pictograms				
STANE	DARD			
ATC	6 IP 65	BATT	1 DAY	