KERN **ORM 1CA**

Digital measurement of refraction index for universal application

Category

Brand	Optics
Product categoriy	Refractometer
Product group	Digital refractometer
Product family	ORM-CA

Measuring System

Measurement temperature [Min] (°C)	0 °C
Measurement temperature [Max] (°C)	40 °C
Precision	0,0003 nD 0,2 % 0,5 °C 0,005 kg/l 0.2 %
Measuring method	Total reflection
Measuring range Brix [Min]	0 %
Scales	Refractive index Brix CW BF AdBlue®
Measuring ranges	1,3330 nD - 1,4200 nD 0,0 % - 50,0 % -60,0 °C - 0,0 °C 1,000 kg/l - 1,500 kg/l 0,0 % - 51,0 %
Readabilites [d]	0,0001 nD 0,1 % 0,1 °C 0,001 kg/l 0,1 %
Readout Brix	0,1 %
Automatic temperature compensation (ATC)	✓
Accuracy Brix	±0,2 %
Scale windshield washer fluid	✓
Measuring range AdBlue® [Min]	0 %
Measuring range AdBlue® [Max]	51 %
Readout AdBlue®	0,1 %
Accuracy AdBlue®	±0,2 %
Measuring range batterie fluid [Min]	1,000 kg/l
Meausring range batterie fluid [Max]	1,500 kg/l
Readout batterie fluid	0,001 kg/l
Accuracy batterie fluid	±0,005 kg/l
Scale for AdBlue®	✓
Measuring range refractive index [Min]	1,3330 nD
Scale batterie fluid	✓
Measuring range refractive index [Max]	1,4200 nD
Readout refractive index	0,0001 nD
Accuracy refractive index	±0,0003 nD
Scale for Refractive index	✓
Measuring range windshield washer fluid [Min]	-60 °C
Measuring range windshield washer fluid [Max]	0 °C
Readout windshield washer fluid	0,1 °C
Accuracy windshield washer fluid	±0,5 °C
Appropriate calibration liquid	0 % (distilled water)
Measuring range Brix [Max]	50 %
Brix scale	✓
Area of application	Automotive

Construction

Dimension (W×D×H)	121×58×25 mm
Refractometer type	Handheld refractometer
Scale - Display type	Digital
Prism lid	✓
Material prism	ZLaF3 lanthanum flint glass nd=1.85544

Functions

Averaging measurement	✓
Averaging measurement amount	15
IP protection - complete device	IP65
Auto-off interval(s) in battery mode/rechargeable battery mode	60 sec

Power Supply

Supplied power supply	Battery

Power supply cable removable	removable
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Pad + Spring
Battery capacity	1.300 mAh
Battery voltage	1,5 V
Battery – Number of cells	1
Battery – Individual weight	11,5 g
Battery – Total weight	11,5 g
Battery – Construction	Individual cells
Battery capacity (Wh)	1,95 Wh
Battery – Lithium content	0 g
Battery/Accu connected	not connected, enclosed

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓

Services (optional)

Article number for factory calibration	961-290

Packing & Shipping

Dimensions transport container (W×D×H)	170×110×50 mm
Delivery time	1 d
Dimensions packaging (W×D×H)	170×110×50 mm
Shipping method	Parcel service
Net weight approx.	0,15 kg
Gross weight approx.	0,35 kg
Shipping weight	0,31 kg

Product information

GTIN/EAN number	4045761335462
REACH classification	no prohibited substances

Pictograms

STANDARD