

VOLTCRAFT - TOP PERFORMANCE IN EVERY WAY

For more than 40 years, our product range has been dynamically adapting to the constant changes in the industry. We commit to offering first-class quality to our customers while delivering an excellent cost-performance ratio. This philosophy remains the cornerstone of Voltcraft's success.

PLS-205S **Platform Scale**



Item no: 3089011

The product is a platform scale with a detachable display unit.

FEATURES

Detachable display unit // Stainless steel weighing platform // Blue display



TECHNICAL DATA

Product

Power supply	Batteries: 2x 1.5 V AAA Power adaptor: 6.0 V/DC, 1.0 A (inside: +, outside: -)
Min. measuring weight	5 g
Weighing capacity	max. 50 kg
Units of measure	kg:g, kg, g, lb, oz, lb:oz
Resolution	d=1 g
Accuracy	5 g - 10 kg: $\pm 5D$ 10 - 20 kg: $\pm 15D$ 20 - 30 kg: $\pm 20D$ 30 - 50 kg: $\pm 40D$
Automatic power off	after 5 minutes
LCD background colour	Blue
Weighting platform material	Stainless steel
Operating temperature	0 to +40 °C
Operating humidity	20 - 80 % RH
Storage temperature	-10 to +50 °C
Storage humidity	20 - 80 % RH
LCD dimensions	75 x 30 mm
Cable length (extendable)	max. 1.5 m
Weighting platform dimensions	250 x 250 mm
Scale dimensions (L x W x H)	250 x 250 x 50 mm
Product weight (approx.)	2.4 kg (without batteries)

Power adaptor

Data according to EU regulation 2019/1782

Manufacturer	Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau
Commercial registration number	HRB 3896
Model identifier	FJ-SW1160601000DE
Input voltage	100 - 240 V/AC
Input AC frequency	50 - 60 Hz
Output voltage	6.0 V/DC
Output current	1.0 A
Output power	6.0 W
Average active efficiency	78.9 %
Efficiency at low load (10 %)	46.0 %
No-load power consumption	0.10 W

CONTENTS

Scale // Display unit // Connection cable // Power adaptor // 2x AAA batteries // Operating instructions

This is a publication by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92242 Hirschau (www.conrad.com).

All rights including translation reserved. Reproduction by any method (e.g. photocopying, microfilming or the capture in electronic data processing systems) requires prior written approval from the editor. Reprinting, also in part, is prohibited. This publication reflects the technical status at the time of printing.

Copyright by Conrad Electronic SE.

*3089011_V2_0926_en_ds 9007200932057355 I2/O2 en