



POWER ADAPTER W40CC GaN

Fast Charger



Technical details

Colour: white Surface: plastic Input connector: EU connector Input voltage: 100 - 240 V

Input alternating current

frequency: 50 / 60 Hz Connections: USB-C 1, USB-C 2

supports (downwards compatible) Output:

PD 3.0, PPS and QC 4.0

USB-C 1/2: 5.0 V/DC 3.0 A, max. 15.0 W 9.0 V/DC 3.0 A, max. 27.0 W 12.0 V/DC 3.0 A, max. 36.0 W 15.0 V/DC 2.67 A, max. 40.0 W 20.0 V/DC 2.0 A, max. 40.0 W

3.3 – 11.0 V/DC 3.0 A, max. 40.0 W 3.3 – 21.0 V/DC 2.0 A, max. 40.0 W

USB-C 1 + USB-C 2:

5.0 V/DC 3.0 A, max. 15.0 W 9.0 V/DC 2.22 Å, max. 20.0 W

88.57%

USB-C 2: 5.0 V/DC 3.0 A, max. 15.0 W 9.0 V/DC 2.22 A, max. 20.0 W

Total: max. 40.0 W

Average efficiency:

Efficiency at low load (10%):

78.02%

Gutenbergstraße 2 | 49377 Vechta | Germany

Power consumption

at no load: 0.12 W

Dimensions: 35.8 x 35.4 x 91.4 mm

Weight: 80.8 g Packing unit: 2pcs

Product data

Colour	Article no	EAN
white	7804012	4 034303 033348

What is GaN?



GaN adapters are a new type of power adapter that have many advantages compared to conventional, silicon-based adapters, GaN stands for Gallium Nitrite, a material with a higher power density and efficiency. The use of GaN enables smaller power adapters that can also handle higher voltages and currents and even produce less heat.

> This makes our power adapters with GaN technology smaller, faster and above all, more energy efficient!