





KPW-10048-D



Industrial DIN-Rail AC-DC 48V 100W Power Supply



DIN-Rail Dimension



Panel Dimension



Katron Technologies Inc.
15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-chih District, New Taipei City, Taiwan
Tel: 886-2-2698-3878
Fax: 886-2-2698-3873
E-mail: kti@ktinet.com.tw
URL: <http://www.ktinet.com.tw>

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.
This information is subject to change without prior notice.

Key Features:

- Provides Full range AC power input
- Industrial terminal block connectors for AC input and DC output interface
- Efficiency to 92%
- Protections: Short circuit/Over current/Over voltage
- Internal power module with UL60950-1 and TUV EN60950-1 safety approval
- Wide range of operating temperature -30°C ~ 70°C

Specifications:

AC IN Voltage	100 ~ 240VAC, 50/60Hz
DC Output voltage	+48V (+/-1%), 2.1A max.
Output Rated Power	100W max.
Efficiency	92% (Typ.)
Input connectors	Terminal block 3P: L/N/PE
Output connectors	Terminal block 6P: 3 Vout+/Vout- pairs
LEDs	AC input, DC output
Protection	Short circuit, Over current, Over voltage
Environment	Operating Temperature: -30°C ~ 60°C Storage Temperature: -40°C ~ 85°C Relative Humidity: 10% ~ 90% non-condensing
Power Derating	100% @ -30°C ~ 50°C, 75% @ 60°C*
Fan Cooling	No
Mounting Support	DIN-Rail, Panel
Dimensions	42 x 106 x 140 (WxDxH)
Internal Power Module	UL60950-1, TUV60950-1, IEC60950-1 certification
MTBF	181K Hours
Approval	FCC Class A, CE mark Class A, LVD, IEC 60068-2-64 Vibration, IEC 60068-2-27 Shock 50G test

* Measured with air flow 1m/s