

Data Sheet

Compressed air hose



- Length: 100 m
- Colour: Blue, Black, Transparent

Item no.	Model no.	Material	Outer Diameter	Inner diameter	Max. working pressure	Rated vacuum range	Bending radius (Min.)	Operating temperature	Color
2615604	PU4X2.5	Polyurethane	4 mm	2.5 mm	10 bar	-0.3 – 0.4 bar	10 mm	-20 – 80 °C	Blue
3208237	PU4X2.5	Polyurethane	5 mm	2.5 mm	11 bar	-0.3 – 0.4 bar	10 mm	-20 – 80 °C	Black
3208238	PU4X2.5	Polyurethane	6 mm	2.5 mm	12 bar	-0.3 – 0.4 bar	10 mm	-20 – 80 °C	Transparent
2615605	PU6X4	Polyurethane	6 mm	4 mm	10 bar	-0.3 – 0.4 bar	15 mm	-20 – 80 °C	Blue
3208239	PU6X4	Polyurethane	6 mm	4 mm	11 bar	-0.3 – 0.4 bar	15 mm	-20 – 80 °C	Black
3208240	PU6X4	Polyurethane	6 mm	4 mm	12 bar	-0.3 – 0.4 bar	15 mm	-20 – 80 °C	Transparent
2615606	PU8X5	Polyurethane	8 mm	5 mm	10 bar	-0.3 – 0.4 bar	20 mm	-20 – 80 °C	Blue
3208241	PU8X5	Polyurethane	8 mm	5 mm	10 bar	-0.3 – 0.4 bar	20 mm	-20 – 80 °C	Black
3208242	PU8X5	Polyurethane	8 mm	5 mm	10 bar	-0.3 – 0.4 bar	20 mm	-20 – 80 °C	Transparent
2615607	PU8X5.5	Polyurethane	8 mm	5.5 mm	10 bar	-0.3 – 0.4 bar	20 mm	-20 – 80 °C	Blue
3208243	PU8X5.5	Polyurethane	8 mm	5.5 mm	10 bar	-0.3 – 0.4 bar	20 mm	-20 – 80 °C	Black
3208244	PU8X5.5	Polyurethane	8 mm	5.5 mm	10 bar	-0.3 – 0.4 bar	20 mm	-20 – 80 °C	Transparent
2615608	PU10X6.5	Polyurethane	10 mm	6.5 mm	10 bar	-0.3 – 0.4 bar	25 mm	-20 – 80 °C	Blue
3208245	PU10X6.5	Polyurethane	10 mm	6.5 mm	10 bar	-0.3 – 0.4 bar	25 mm	-20 – 80 °C	Black
3208246	PU10X6.5	Polyurethane	10 mm	6.5 mm	10 bar	-0.3 – 0.4 bar	25 mm	-20 – 80 °C	Transparent
2615609	PU12X8	Polyurethane	12 mm	8 mm	10 bar	-0.3 – 0.4 bar	35 mm	-20 – 80 °C	Blue
3208247	PU12X8	Polyurethane	12 mm	8 mm	10 bar	-0.3 – 0.4 bar	35 mm	-20 – 80 °C	Black
3208248	PU12X8	Polyurethane	12 mm	8 mm	10 bar	-0.3 – 0.4 bar	35 mm	-20 – 80 °C	Transparent
2615610	PTFE4X2	PTFE	4 mm	2 mm	10.2 bar	-	-	-80 – 200 °C	Blue
2615611	PTFE6X4	PTFE	6 mm	4 mm	10.2 bar	-	-	-80 – 200 °C	Blue