
















Circuit Diagram

35 1 P
- Zhuhai/China
- 2021 Year
- 35 Week

The date code could be printed on each lateral side randomly

GENERAL CHARACTERISTICS

Operating Force	Max. 45gf
Release Force	Min. 10gf
Contact Resistance	Max. 50mΩ
Insulation Resistance	Min. 100MΩ 500VDC
Dielectric Voltage	AC500V 60 Sec.
Mechanical Life	1,000,000 Cycles
Electrical Life	25,000 Cycles
Rating	3(0.5)A 125/250VAC
Operating Temperature	-25 to 125℃

NO.	PARTS	MATERIALS
01	COVER	PBT 94V0
02	BASE	PBT 94V0
03	ACTUATOR	PBT 94V0
04	CONTACT	Ag ALLOY
05	MOVING BLADE	COPPER BERYLLIUM
06	TERMINAL(COM)	SILVER PLATE BRASS
07	TERMINAL(NO)	SILVER PLATE BRASS
08	TERMINAL(NC)	SILVER PLATE BRASS
09	AUX. ACTUATOR	SUS

Further details please refer to technical specification TS-DG-00001.
In case there are any deviations the drawing details have priority.

3					制图: DRAW	H,QIN	2020.12.11	TOLERANCE UNLESS SPECIFLED		采埃孚电子(珠海)有限公司 ZF Electronics (Zhuhai) Company Limited							
2					设计: DESIGN	H,QIN	2020.12.11	WITHIN 1.5mm: ±0.1mm OVER 1.5mm: ±0.2mm		系列 SERIES	DG 3A微动开关/SUBMINIATURE SWITCH						
1					审核: CHECKED	J.WANG	2020.12.16	材质: MATERIAL		料号: TITLE	DGE3-E7LC			图号: DWG NO.	DGE3-E7LC		
记号 MARK.	变更内容 DEFINITION	修改 REVISE	核准 APPROVE	日期 DATE	批准: APPROVE	J.WANG	2020.12.16	单位: UNIT	mm	比例: SCALE	1:1	角法: PROJ.		张数: SHEET	第1页,共1页	工程图 ENG. DWG	版本: REV. A0