Datasheet

Manufacturer Part No.: T26CA136 … T26CA145

Hook-and-Loop Cable-Tie Sets 300/500 pcs.





These hook-and-loop cable-ties made of polyamide are easy to open and close again. Therefore, they are ideally suited for general bundling tasks and fixations of, for example, objects, cables, sports utensils, plants, curtains, tools and much more. The excellent material properties of polyamide allow a wide range of applications as far as environmental conditions are concerned. The material is dimensionally stable, robust and resistant to many liquids and also UV radiation. The supply set of 10 hook-and-loop cable ties with eyelet content is optimal for any indoor and outdoor applications. The black design can be unrestricted and inconspicuous in many usages.

Technical data:

Material: Polyamide • Temperature range: -20 ... 85 °C • Melting temperature: >250 °C • Color: black.

Part-No.	Description	Length	Width	Color	Content	EAN / GTIN
T26CA136	Hook & loop cable-ties 100/150/200 mm x 12 mm	100 mm (100x) 150 mm (100x) 200 mm (100x)	12 mm	Black	300 pcs.	4262511626773
T26CA137	Hook & loop cable-ties 100/150/200 mm x 12 mm	100 mm (200x) 150 mm (200x) 200 mm (100x)	12 mm	Black	500 pcs.	4262511626780
T26CA138	Hook & loop cable-ties 100/150/200/250/300 mm x 12 mm	100 mm (100x) 150 mm (100x) 200 mm (100x) 250 mm (100x) 300 mm (100x)	12 mm 14 mm	Black	500 pcs.	4262511626797
T26CA139	Hook & loop cable-ties 100 mm x 12 mm	100 mm (500x)	12 mm	Black	500 pcs.	4262511626803
T26CA140	Hook & loop cable-ties 150 mm x 12 mm	150 mm (500x)	12 mm	Black	500 pcs.	4262511626810
T26CA141	Hook & loop cable-ties 200 mm x 12 mm	200 mm (500x)	12 mm	Black	500 pcs.	4262511626827
T26CA142	Hook & loop cable-ties 250 mm x 12 mm	250 mm (500x)	12 mm	Black	500 pcs.	4262511626834
T26CA143	Hook & loop cable-ties 300 mm x 14 mm	300 mm (500x)	14 mm	Black	500 pcs.	4262511626841
T26CA144	Hook & loop cable-ties 350 mm x 14 mm	350 mm (500x)	14 mm	Black	500 pcs.	4262511626858
T26CA145	Hook & loop cable-ties 400 mm x 16 mm	400 mm (500x)	16 mm	Black	500 pcs.	4262511626865

This is a publication by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com).

All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval of the editor. Reprinting, also in part, is prohibited. The publication represents the technical status at the time of printing. All statements without guarantee.

© Conrad Electronic SE