

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 27/08/2024 Revision date: 27/08/2024 Supersedes version of: 22/02/2024 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	: MULTILUBE PRO
UFI	: 7S0Y-48UP-E008-ARYT
Product code	: BDS001857AE
Vaporizer	: Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category Use of the substance/mixture Professional uselubricants

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V. Touwslagerstraat 1 9240 Zele Belgium T +32(0)52/45.60.11, F +32(0)52/45.00.34 hse@crcind.com, www.crcind.com

1.4. Emergency telephone number

Emergency number

: +32(0)52/45.60.11 Office hours: 9-17h CET

Country/Area	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3,	H336
Narcosis	
Hazardous to the aquatic environment – Chronic Hazard,	H411
Category 2	
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Pressurized container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2	2008 [CLP]
Hazard pictograms (CLP)	
	GHS02 GHS07 GHS09
Signal word (CLP)	: Danger
Contains	: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Hazard statements (CLP)	: H222 - Extremely flammable aerosol.
	H229 - Pressurised container: May burst if heated.
	H315 - Causes skin irritation.
	H319 - Causes serious eye irritation.
	H336 - May cause drowsiness or dizziness.
	H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P102 - Keep out of reach of children.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
	P211 - Do not spray on an open flame or other ignition source.
	P251 - Do not pierce or burn, even after use.
	P261 - Avoid breathing vapours/spray.
	P280 - Wear protective gloves/eye protection.
	P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
	P501 - Dispose of contents/container to a hazardous or special waste collection point, in
	accordance with local, regional, national and/or international regulation.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propane substance with national workplace exposure limit(s) (BE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944- 21	25 – 50	Flam. Gas 1, H220 Press. Gas (Liq.), H280
butane substance with national workplace exposure limit(s) (BE)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	25 – 50	Flam. Gas 1, H220 Press. Gas (Liq.), H280
isobutane substance with national workplace exposure limit(s) (BE)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395- 27	10 – 25	Flam. Gas 1, H220 Press. Gas (Liq.), H280

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC-No.: 921-024-6 REACH-no: 01-2119475514- 35	10 – 25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (Note L)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077- 29	5 – 10	Asp. Tox. 1, H304
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	CAS-No.: 4259-15-8 EC-No.: 224-235-5 REACH-no: 01-2119493635- 27	< 3	Eye Dam. 1, H318 Aquatic Chronic 2, H411

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	CAS-No.: 4259-15-8 EC-No.: 224-235-5 REACH-no: 01-2119493635- 27	(50 ≤ C < 100) Eye Dam. 1; H318

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and ef	ffects, both acute and delayed
Symptoms/effects Symptoms/effects after skin contact Symptoms/effects after eye contact	: May cause drowsiness or dizziness. : Irritation. : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Do not use a heavy water stream.	
5.2. Special hazards arising from the subst	tance or mixture	
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Extremely flammable aerosol. Pressurized container: May burst if heated. During fire, gases hazardous to health may be formed. 	
5.3. Advice for firefighters		
Firefighting instructions Protection during firefighting	 Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. 	

SECTION 6: Accidental release measures		
6.1. Personal precautions, prote	ctive equipment and emergency procedures	
For non-emergency personnel		
Protective equipment	: Wear appropriate protective equipment and clothing during clean-up.	
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.	
For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
Emergency procedures	Evacuate unnecessary personnel. Ventilate area.	

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

with wet sand or	over the product. For large spills, confine the spill in a dike and charge it earth for subsequent safe disposal. Following product recovery, flush area
with wet sand or	
with water. Take remove residual o	up small spills with dry chemical absorbent. Clean surface thoroughly to
Other information : Dispose of mater	als or solid residues at an authorized site.

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industria hygiene and safety procedures.	
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked
	up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated
	place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

propane (74-98-6)		
Belgium - Occupational Exposure Limits		
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)	
OEL TWA	1000 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
isobutane (75-28-5)		
Belgium - Occupational Exposure Limits		
Local name	Butane, tous isomères: iso-butane # Butaan, alle isomeren: iso-butaan	
OEL STEL	2370 mg/m ³	
	980 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
butane (106-97-8)		
Belgium - Occupational Exposure Limits		
Local name	Butane, tous isomères: n-butane # Butaan, alle isomeren: n-butaan	
OEL STEL	2370 mg/m³	
	980 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	

DNEL and PNEC

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2035 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	699 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	608 mg/m³	
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day	
Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0,97 mg/kg bodyweight/day	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)		
Long-term - systemic effects, inhalation	2,73 mg/m³	
Long-term - local effects, inhalation	5,58 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0,74 mg/kg bodyweight/day	
PNEC (Oral)		
PNEC oral (secondary poisoning)	9,33 mg/kg food	

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Skin protection

Skin and body protection: Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

Not availableNot applicable

Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties	
9.1. Information on basic physical and chemical properties	
Physical state	: Liquid
Colour	: Blue.
Appearance	: Propane/butane propelled liquid.
Odour	: Solvent.

Odour threshold

Melting point

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurized container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: -35 °C (closed cup)
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
рН	: Not applicable
Viscosity, kinematic	: 45 mm²/s
Viscosity, dynamic	: 36 mPa·s at 40 °C
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,8 g/cm³ at 20 °C
Relative density	: 0,8 at 20 °C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

50 – 75 %
510 g/l
For aerosols data for the product without propellant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

SECTION 11: Toxicological information	
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008	
Acute toxicity (oral)	• Not classified (Based on available data, the classification criteria are not met)

Acute toxicity	(oral)
Acute toxicity	(dermal)
Acute toxicity	(inhalation)

Not classified (Based on available data, the classification criteria are not met)
Not classified (Based on available data, the classification criteria are not met)

: Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
LD50 oral rat	5841 mg/kg	
LD50 dermal rat	2800 – 3100 mg/kg bodyweight	
LC50 Inhalation - Rat	> 25,2 mg/l/4h	
Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)		
LD50 oral rat	> 5000 mg/kg bodyweight	
LD50 dermal rabbit	> 2000 mg/kg	
Zinc bis[0,0-bis(2-ethylhexyl)] bis(dithioph	osphate) (4259-15-8)	
LD50 oral rat	3100 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg bodyweight	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	pH: Not applicable: Causes serious eye irritation.pH: Not applicable	
Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity Reproductive toxicity STOT-single exposure	 Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) May cause drowsiness or dizziness. 	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)	
Distillates (petroleum), hydrotreated light pa	araffinic; Baseoil— unspecified (64742-55-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0,98 mg/l air	
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)		
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight	
Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)		
MULTILUBE PRO		
Vaporizer	Aerosol	
Viscosity, kinematic	45 mm²/s	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Viscosity, kinematic	0,7 mm²/s	
11.2. Information on other hazards		
Endocrine disrupting properties		
Adverse health effects caused by endocrine	: The mixture does not contain substance(s) included in the list established in accordance	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1.	Toxicity
	1 OAIOILY

·_···	
Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term	: Not classified (Based on available data, the classification criteria are not met)
(acute)	
Hazardous to the aquatic environment, long-term	: Toxic to aquatic life with long lasting effects.
(chronic)	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
LC50 - Fish [1]	11,4 mg/l	
EC50 - Crustacea [1]	3 mg/l	
EC50 72h - Algae [1]	10 mg/l	
LOEC (chronic)	0,32 mg/l	
NOEC (chronic)	0,17 mg/l	
NOEC chronic fish	2,04 mg/l	
NOEC chronic crustacea	1 mg/l	
Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)		
LC50 - Fish [1]	> 5000 mg/l	
EC50 - Crustacea [1]	> 1000 mg/l	
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)		
LC50 - Fish [1]	46 mg/l Cyprinodon variegatus	

12.2. Persistence and degradability

MULTILUBE PRO			
Persistence and degradability	Not established. No data is available on the degradability of this product.		
propane (74-98-6)			
Persistence and degradability	Not rapidly degradable		
isobutane (75-28-5)			
Persistence and degradability	Not rapidly degradable		
butane (106-97-8)			
Persistence and degradability	Not rapidly degradable		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Persistence and degradability	Not rapidly degradable		
Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)			
Persistence and degradability	Not rapidly degradable		
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)			
Persistence and degradability	Not rapidly degradable		
12.3. Bioaccumulative potential			

MULTILUBE PRO

Partition coefficient n-octanol/water (Log Kow)

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified (64742-55-8)	
---	--

Partition coefficient n-octanol/water (Log Pow)	3,9 - 6
---	---------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment		
MULTILUBE PRO		
Results of PBT assessment	Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII	
12.6. Endocrine disrupting properties		
Adverse effects on the environment caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.	
12.7. Other adverse effects		
	: No other effects known : 1.67 (Fluorinated greenhouse gases - (EC) No 2024/573)	

SECTION 13: Disposal consideration	is
13.1. Waste treatment methods	
Waste treatment methods European List of Waste (LoW, EC 2000/532)	 Dispose of contents/container in accordance with licensed collector's sorting instructions. According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

n accordance with ADR / IMDG / IATA / ADN / RID				
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID n	umber			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard o	class(es)			
2.1	2.1	2.1	2.1	2.1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

IMDG	ΙΑΤΑ	ADN	RID
Not applicable	Not applicable	Not applicable	Not applicable
zards			
Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
	Not applicable zards Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-D	Not applicable Not applicable zards Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-D	Not applicable Not applicable Not applicable zards Dangerous for the environment: Yes Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-D

14.6. Special precautions for user

Overland transport	
Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 11
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading	: CV9, CV12
and handling (ADR)	
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D
Transport by sea	
Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69
Air transport	
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L
Inland waterway transport	
Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 190, 327, 344, 023 : 1L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading	: CW9, CW12
and handling (RID)	
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

VOC content

: 510 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Abbreviations a	and acronyms:
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EU	1-statements:
Aerosol 1	Aerosol, Category 1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity - Single exposure, Category 3, Narcosis

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.