


# Separate units $\varnothing$ 22: Heads

IP 66  
 To be combined with a clip, LED block and contact blocks (p. 48)  
 With locking ring  
 Plastic chrome bezel  
 Black bezel on request (form p. 79)  
 Conform to IEC 60947-5-1

 Characteristics (p. 94)  
 Cross reference list (p. 311)


## ► PUSH-BUTTONS - ILLUMINATED (CONTINUED)

### SPRING RETURN - PROJECTING

Cat. No.



L21AK20



- Red
- Green
- Yellow
- White
- Blue


- L21AK10**
- L21AK20**
- L21AK40**
- L21AK50**
- L21AK60**

### SPRING RETURN - MUSHROOM HEAD $\varnothing$ 32

Push



L21AL10



- Red
- Green
- Yellow
- White


- L21AL10**
- L21AL20**
- L21AL40**
- L21AL50**

### SPRING RETURN - FLUSH-FLUSH



Double touch



L61QH21



Central part illuminated

-  Green
-  Red
- Green
- Green
- Green engraving START
- Red engraving STOP


**L61QH21**

**L61QH22V**

**L61QH21A**

# Panel cut-out

## DRILLING




For heads equipped with electrical blocks with screw or plug-in terminals


### Minimum interval (mm)

	= 30	With or without legend (usual case)
	= 33	IP 67 (silicon shroud)
	= 40	With large legend plate
<b>A</b>	> 40	For mushroom head $\varnothing$ 40
	> 45	For selector switch with long handle
	= 38	For super-flush button
	= 50	With 5 position clip
<b>B</b>	= 45	With or without legend plate (usual case)
	= 54	With double touch
	= 77	With double touch + legend plate
	= 50	Joystick

## DRILLING FOR SUPER-FLUSH BUTTON




## DRILLING WHEN USING THE ANTI-ROTATION RING (OPTIONAL)




## THICKNESS OF PANEL (E)

E = 1 to 6 mm




# Mounting blocks $\varnothing 22$

NON ILLUMINATED



# Mounting blocks $\varnothing 22$

## ILLUMINATED



# Technical characteristics

## ▶ GENERAL

Characteristics	Data	Standards
▶ Storage temperature	- 40 °C to + 70 °C	
▶ Operating temperature	- 25 °C to + 70 °C	
▶ Climatic resistance	Constant humid heat Cyclic damp heat Resistance to sea air	IEC 60068-2-3 IEC 60068-2-30 IEC 60068-2-52
▶ Degree of protection	IP 66 for standard heads IP 67 for shrouded heads IP 66 for equipped control stations IP 20 at the rear of the panel for contact blocks and one piece pilot lights Type 1, 2, 3, 3R, 3S, 4, 4X, 12, and 13 for heads and control stations	IEC 60529     NEMA standard
▶ Protection against mechanical impacts	IK 05 illuminated and non illuminated heads IK 07 empty control station	IEC 62262
▶ Electrical insulation	Class II - heads and control station	IEC 60947-5-1
▶ Terminal marking		IEC 60947-1
▶ Tightening torques	Locking ring: recommended 3 N.m terminals: max. 1.2 N.m	
▶ Approvals	UL United states and Canada BV Bureau Véritas Certification OC/CB	UL 508, CSA 22.2 Marine rules IEC 60947-5-1 IEC 60947-5-5 IEC 60947-5-4
▶ Vibrations	withstand vibration Fc test: 2 to 25 Hz, 1.6 mm; 25-100 Hz, 4 g	IEC 60068-2-6

# Technical characteristics

## ▶ CONTACT BLOCKS

Screw and plug-in connection characteristics	Data	Standards	
▶ Rated insulation voltage	690 V AC 600 V AC	IEC/EN 60947-1 UL 508	
▶ NC contacts	Positive opening	IEC/EN 60947-5-1	
▶ Rated impulse voltage U <sub>imp</sub> Pollution degree	6kV 3		
▶ Conventional thermal current in free air conditions	AC15: 10 A DC13: 2,5 A	IEC 60947-5-1	
▶ Electrical ratings	<p><b>Alternating current</b> AC15 - A 600 U<sub>e</sub> = 120 V, I<sub>e</sub> = 6 A U<sub>e</sub> = 240 V, I<sub>e</sub> = 3 A U<sub>e</sub> = 380 V, I<sub>e</sub> = 1,9 A U<sub>e</sub> = 480 V, I<sub>e</sub> = 1,5 A U<sub>e</sub> = 500 V, I<sub>e</sub> = 1,4 A U<sub>e</sub> = 600 V, I<sub>e</sub> = 1,2 A</p> <p><b>Minimum operating current</b> - standard blocks U<sub>e</sub> = 24 V DC and I<sub>e</sub> = 5 mA Failure rate &lt; 10<sup>-8</sup></p>	<p><b>Direct current</b> DC13 - Q 600 U<sub>e</sub> = 125 V, I<sub>e</sub> = 0,55 A U<sub>e</sub> = 250 V, I<sub>e</sub> = 0,27 A U<sub>e</sub> = 400 V, I<sub>e</sub> = 0,15 A U<sub>e</sub> = 500 V, I<sub>e</sub> = 0,13 A U<sub>e</sub> = 600 V, I<sub>e</sub> = 0,1 A</p> <p>- golden contacts U<sub>e</sub> = 5 V DC and I<sub>e</sub> = 1 mA Failure rate &lt; 10<sup>-8</sup></p>	IEC 60947-5-1
▶ Electrical operating life	<p><b>1 million cycles for:</b> - AC15 - B 300 U<sub>e</sub> = 120 V, I<sub>e</sub> = 3 A U<sub>e</sub> = 240 V, I<sub>e</sub> = 1,5 A</p>	<p>- DC13 - R 300 U<sub>e</sub> = 125 V, I<sub>e</sub> = 0,22 A U<sub>e</sub> = 250 V, I<sub>e</sub> = 0,1 A</p>	
▶ Applicable wire sizes	Rigid or flexible wire without ferrule: 0,5 mm <sup>2</sup> to 2 x 2,5 mm <sup>2</sup> Rigid or flexible wire with ferrule: 0,5 mm <sup>2</sup> to 2 x 1,5 mm <sup>2</sup>		
Faston connection	Data	Standards	
▶ Rated insulation voltage	320 V AC 300 V AC	IEC/EN60947-1 UL 508	
▶ NC contacts	Positive opening	IEC/EN 60947-5-1	
▶ Rated impulse withstanding voltage U <sub>imp</sub> Pollution degree	6 kV 3		
▶ Conventional thermal current in free air conditions	AC 15: 10 A DC 13: 2,5 A	IEC 60947-5-1	
▶ Electrical ratings	<p><b>Alternating current</b> AC15 - A 300 U<sub>e</sub> = 120 V, I<sub>e</sub> = 6 A U<sub>e</sub> = 240 V, I<sub>e</sub> = 3 A</p> <p><b>Minimum current of use</b> U<sub>e</sub> = 24 V DC and I<sub>e</sub> = 5 mA Failure rate &lt; 10<sup>-8</sup></p>	<p><b>Direct current</b> DC13 - Q 300 U<sub>e</sub> = 125 V, I<sub>e</sub> = 0,55 A U<sub>e</sub> = 250 V, I<sub>e</sub> = 0,27 A</p> <p>- DC13 - R 300 U<sub>e</sub> = 125 V, I<sub>e</sub> = 0,22 A U<sub>e</sub> = 250 V, I<sub>e</sub> = 0,1 A</p>	IEC 60947-5-1
▶ Electrical operating life	<p><b>1 million cycles for:</b> - AC15 - B 300 U<sub>e</sub> = 120 V, I<sub>e</sub> = 3 A U<sub>e</sub> = 240 V, I<sub>e</sub> = 1,5 A</p>	<p>- DC13 - R 300 U<sub>e</sub> = 125 V, I<sub>e</sub> = 0,22 A U<sub>e</sub> = 250 V, I<sub>e</sub> = 0,1 A</p>	
▶ Faston size	6,35 mm or 2 x 2,8 mm		

# Technical characteristics

## ▶ CONTACT BLOCKS

Pin-style connection (for PCB)	Data	Standards	
▶ Rated insulation voltage	250 V AC 250 V AC	IEC/EN60947-1 UL 508	
▶ NC contacts	Positive opening	IEC/EN 60947-5-1	
▶ Rated impulse withstanding voltage Uimp Pollution degree	4 kV 3		
▶ Conventional thermal current in free air conditions	AC 15: 5 A DC 13: 1 A	IEC 60947-5-1	
▶ Electrical ratings	<b>Alternating current</b> AC 15 - B 300 Ue = 120 V, Ie = 3 A Ue = 240 V, Ie = 1,5 A	<b>Direct current</b> DC13 - R 300 Ue = 125 V, Ie = 0,22 A Ue = 250 V, Ie = 0,1 A	IEC 60947-5-1 IEC 60947-5-4
	<b>Minimum current of use</b> - standard blocks Ue = 24 V DC and Ie = 5 mA Failure rate < 10 <sup>-8</sup>	- golden contacts Ue = 5 V DC and Ie = 1 mA Failure rate < 10 <sup>-8</sup>	
▶ Electrical operating life	<b>1 million cycles for:</b> - AC15 - B 300 Ue = 120 V, Ie = 3 A Ue = 240 V, Ie = 1,5 A	- DC13 - R 300 Ue = 125 V, Ie = 0,22 A Ue = 250 V, Ie = 0,1 A	
▶ Pin diameter	∅ 1 mm		

## ▶ LED BLOCKS FOR ILLUMINATED HEADS AND ONE PIECE LED PILOT LIGHTS

Characteristics	Data	Standards
▶ Rated insulation voltage	300 V	IEC/EN 60947-5-1
▶ Rated impulse voltage Uimp Pollution degree	4 kV (with filter block see p. 64) 3	IEC/EN 60947-5-1
▶ Operating voltage	12 to 24 V AC/DC 48 V AC/DC (for LED block) 130 V AC 230 V AC	
▶ Frequency	50 or 60 Hz	
▶ Lifetime at rated supply voltage	Red and yellow: 100 000 hours at 25 °C Other colours: 50 000 hours at 25 °C	
▶ Consumption of LED blocks	Voltage: - 24 V: 25 mA ± 20% - 48 V: 15 mA ± 5% - 130 V: 20 mA ± 10% - 230 V: 16 mA ± 30%	

# Technical characteristics

## ▶ ONE PIECE PILOT LIGHT BA9S

Characteristics	Data	Standards
▶ Rated insulation voltage	400 V	IEC 60947-5-1
▶ Rated impulse withstand voltage Uimp	4 kV	IEC/EN 60947-1
▶ Bulb rating	400 V max. - 2,6 W max. 240 V max. - 2,6 W max.	IEC 60947-5-1 UL 508

## ▶ HEADS

Characteristics	Data	Standards
▶ Mechanical endurance (in million cycles)	Spring return: 5 Push-push: 0,5 Selector switches: 0,3 Mushroom head maintained function EN 418: 0,10 Mushroom head maintained function: 0,15	
▶ Activation force in N	Spring return + NO: 6,5 Spring return + NC: 4,5 Additional NO contact: 4,5 Additional NC contact: 3,0 Push-pull mushroom head + NO + NC: 27 Push-turn mushroom head + NO + NC: 22 Push-pull mushroom head EN 418 + NO + NC: 37 Push-turn mushroom head EN 418 + NO + NC: 60	
▶ Activation force in Nm	Selector switch + NO: 0,04 Additional NO contact: 0,03	

## ▶ EMERGENCY STOP ACTUATORS - EN 418:

For equipment subject to Machine Security Directive CE 98/37 and EN60204 standard.

BACO emergency stop switches EN418 and contact blocks meet the requirements of the European Machine Directive EN 418 and EN60947-5-5 specification.

Our E-stops provide the "fool-proof" or "tease-proof" emergency stop switch feature - described below, that latches in the emergency stop command and then switches the contact state to open the circuit and shut down the equipment.

"After the emergency stop command has been generated during actuation of the emergency stop device, the command shall be maintained by engagement (latching-in) of the actuating means. The emergency stop command shall be maintained until the emergency stop device is reset (disengaged). It shall not be possible for the emergency stop device to engage without generating the stop command."

Simply stated, this directive indicates that the latching mechanism of the switch is activated when the actuator is pushed to a certain point. The switch will continue to remain in this latched position until manually reset by twisting to release.



# Diagrams

## MECHANICAL OPERATION

For 3 position selector switches

Handle position  
(front side view)



Contacts block actuation  
(back view)



Back side view

Non operated block


Operated block




## MECHANICAL OPERATION

For Joysticks

2 positions




4 positions




## PUSH-TO-TEST LED PILOT LIGHT DIAGRAMS


Lamp-testing module with 1 diode (33ET) for direct supply 24 V and 48 V




Lamp-testing module with 2 diodes (33ETT) for direct supply 24 V and 48 V



Lamp-testing assembly for direct supply 130 V and 240 V (Consult us - see page 79)



## PRINTED CIRCUIT BOARD MOUNTING



# Frontelemente $\varnothing$ 22

IP 66  
 Mit Befestigungsmutter  
 Zur Kombination mit einem Adapter und Kontaktelementen (Seite 48)  
 Frontring Kunststoff verchromt - schwarzer Frontring auf Anfrage (siehe Formular Seite 79)  
 Nach Norm EN-IEC 60947-5-1



Technische Daten (Seite 94)  
 Vergleichstabelle (Seite 311)


## ► DRUCKTASTER - BELEUCHTBAR

### TASTEND - HOCH

Bestell-Nr.



L21AK20



- Rot
- Grün
- Gelb
- Weiß
- Blau


- L21AK10
- L21AK20
- L21AK40
- L21AK50
- L21AK60

### TASTEND - PILZTASTER $\varnothing$ 32

Bestell-Nr.



L21AL10



- Rot
- Grün
- Gelb
- Weiß

- L21AL10
- L21AL20
- L21AL40
- L21AL50


### TASTEND - FLACH-FLACH

### Doppeldrucktaster

Bestell-Nr.



L62QH21




Meldeleuchte in der Mitte

- Grün
- Rot
- Grün
- Grün
- Grün Bezeichnung START
- Rot Bezeichnung STOP

- L62QH21
- L62QH22V
- L62QH21A

# Separate units $\varnothing$ 22: Heads

IP 66  
 To be combined with a clip and electrical blocks (p. 48)  
 Equipped with a locking ring  
 Plastic black bezel  
 Conform to IEC 60947-5-1

 Characteristics (p. 94)  
 Cross reference list (p. 311)

## ► EN 418/ISO 13850 EMERGENCY STOP - NON ILLUMINATED (CONTINUED)


$\varnothing$  40 EN 418/ISO 13850 - STAY-PUT

Push-pull to reset

Cat. No.



L22DR01



Head position visible from the side with yellow collar  
 Compliant with the requirements of emergency stop:  
 IEC 60947-5-5 / EN 418/ISO 13850

● Red


**L22DR01**

$\varnothing$  40 EN 418/ISO 13850 - STAY-PUT

Push-turn to reset



L22ER01



Head position visible from the side with yellow collar  
 Compliant with the requirements of emergency stop:  
 IEC 60947-5-5 / EN 418/ISO 13850

● Red


**L22ER01**

$\varnothing$  40 EN 418/ISO 13850 - STAY-PUT

Key to reset



L22GR01



Supplied with 2 keys profile n° 455  
 Head position visible from the side with yellow collar  
 Compliant with the requirements of emergency stop:  
 IEC 60947-5-5 / EN 418/ISO 13850

● Red


**L22GR01**

$\varnothing$  54 EN 418/ISO 13850 - STAY-PUT

Push-pull to reset with flag indicator



L22DU01




Double position indicator: head and collar  
 Compliant with the requirements of emergency stop:  
 IEC 60947-5-5 / EN 418/ISO 13850

● Red - engraving O - I  
 ● Red - engraving STOP - I

**L22DU01A**  
**L22DU01**

# Panel cut-out

## DRILLING




For heads equipped with electrical blocks with screw or plug-in terminals


### Minimum interval (mm)

	= 30	With or without legend (usual case)
	= 33	IP 67 (silicon shroud)
	= 40	With large legend plate
<b>A</b>	> 40	For mushroom head $\varnothing$ 40
	> 45	For selector switch with long handle
	= 38	For super-flush button
	= 50	With 5 position clip
<b>B</b>	= 45	With or without legend plate (usual case)
	= 54	With double touch
	= 77	With double touch + legend plate
	= 50	Joystick

## DRILLING FOR SUPER-FLUSH BUTTON




## DRILLING WHEN USING THE ANTI-ROTATION RING (OPTIONAL)




## THICKNESS OF PANEL (E)

E = 1 to 6 mm




# Mounting blocks $\varnothing 22$

NON ILLUMINATED



# Mounting blocks $\varnothing 22$

## ILLUMINATED



# Technical characteristics

## ▶ GENERAL

Characteristics	Data	Standards
▶ Storage temperature	- 40 °C to + 70 °C	
▶ Operating temperature	- 25 °C to + 70 °C	
▶ Climatic resistance	Constant humid heat Cyclic damp heat Resistance to sea air	IEC 60068-2-3 IEC 60068-2-30 IEC 60068-2-52
▶ Degree of protection	IP 66 for standard heads IP 67 for shrouded heads IP 66 for equipped control stations IP 20 at the rear of the panel for contact blocks and one piece pilot lights Type 1, 2, 3, 3R, 3S, 4, 4X, 12, and 13 for heads and control stations	IEC 60529    NEMA standard
▶ Protection against mechanical impacts	IK 05 illuminated and non illuminated heads IK 07 empty control station	IEC 62262
▶ Electrical insulation	Class II - heads and control station	IEC 60947-5-1
▶ Terminal marking		IEC 60947-1
▶ Tightening torques	Locking ring: recommended 3 N.m terminals: max. 1.2 N.m	
▶ Approvals	UL United states and Canada BV Bureau Véritas Certification OC/CB	UL 508, CSA 22.2 Marine rules IEC 60947-5-1 IEC 60947-5-5 IEC 60947-5-4
▶ Vibrations	withstand vibration Fc test: 2 to 25 Hz, 1.6 mm; 25-100 Hz, 4 g	IEC 60068-2-6

# Technical characteristics

## ▶ CONTACT BLOCKS

Screw and plug-in connection characteristics	Data	Standards	
▶ Rated insulation voltage	690 V AC 600 V AC	IEC/EN 60947-1 UL 508	
▶ NC contacts	Positive opening	IEC/EN 60947-5-1	
▶ Rated impulse voltage U <sub>imp</sub> Pollution degree	6kV 3		
▶ Conventional thermal current in free air conditions	AC15: 10 A DC13: 2,5 A	IEC 60947-5-1	
▶ Electrical ratings	<p><b>Alternating current</b> AC15 - A 600 U<sub>e</sub> = 120 V, I<sub>e</sub> = 6 A U<sub>e</sub> = 240 V, I<sub>e</sub> = 3 A U<sub>e</sub> = 380 V, I<sub>e</sub> = 1,9 A U<sub>e</sub> = 480 V, I<sub>e</sub> = 1,5 A U<sub>e</sub> = 500 V, I<sub>e</sub> = 1,4 A U<sub>e</sub> = 600 V, I<sub>e</sub> = 1,2 A</p> <p><b>Minimum operating current</b> - standard blocks U<sub>e</sub> = 24 V DC and I<sub>e</sub> = 5 mA Failure rate &lt; 10<sup>-8</sup></p>	<p><b>Direct current</b> DC13 - Q 600 U<sub>e</sub> = 125 V, I<sub>e</sub> = 0,55 A U<sub>e</sub> = 250 V, I<sub>e</sub> = 0,27 A U<sub>e</sub> = 400 V, I<sub>e</sub> = 0,15 A U<sub>e</sub> = 500 V, I<sub>e</sub> = 0,13 A U<sub>e</sub> = 600 V, I<sub>e</sub> = 0,1 A</p> <p>- golden contacts U<sub>e</sub> = 5 V DC and I<sub>e</sub> = 1 mA Failure rate &lt; 10<sup>-8</sup></p>	IEC 60947-5-1
▶ Electrical operating life	<p><b>1 million cycles for:</b> - AC15 - B 300 U<sub>e</sub> = 120 V, I<sub>e</sub> = 3 A U<sub>e</sub> = 240 V, I<sub>e</sub> = 1,5 A</p>	<p>- DC13 - R 300 U<sub>e</sub> = 125 V, I<sub>e</sub> = 0,22 A U<sub>e</sub> = 250 V, I<sub>e</sub> = 0,1 A</p>	
▶ Applicable wire sizes	Rigid or flexible wire without ferrule: 0,5 mm <sup>2</sup> to 2 x 2,5 mm <sup>2</sup> Rigid or flexible wire with ferrule: 0,5 mm <sup>2</sup> to 2 x 1,5 mm <sup>2</sup>		
Faston connection	Data	Standards	
▶ Rated insulation voltage	320 V AC 300 V AC	IEC/EN60947-1 UL 508	
▶ NC contacts	Positive opening	IEC/EN 60947-5-1	
▶ Rated impulse withstanding voltage U <sub>imp</sub> Pollution degree	6 kV 3		
▶ Conventional thermal current in free air conditions	AC 15: 10 A DC 13: 2,5 A	IEC 60947-5-1	
▶ Electrical ratings	<p><b>Alternating current</b> AC15 - A 300 U<sub>e</sub> = 120 V, I<sub>e</sub> = 6 A U<sub>e</sub> = 240 V, I<sub>e</sub> = 3 A</p> <p><b>Minimum current of use</b> U<sub>e</sub> = 24 V DC and I<sub>e</sub> = 5 mA Failure rate &lt; 10<sup>-8</sup></p>	<p><b>Direct current</b> DC13 - Q 300 U<sub>e</sub> = 125 V, I<sub>e</sub> = 0,55 A U<sub>e</sub> = 250 V, I<sub>e</sub> = 0,27 A</p> <p>- DC13 - R 300 U<sub>e</sub> = 125 V, I<sub>e</sub> = 0,22 A U<sub>e</sub> = 250 V, I<sub>e</sub> = 0,1 A</p>	IEC 60947-5-1
▶ Electrical operating life	<p><b>1 million cycles for:</b> - AC15 - B 300 U<sub>e</sub> = 120 V, I<sub>e</sub> = 3 A U<sub>e</sub> = 240 V, I<sub>e</sub> = 1,5 A</p>	<p>- DC13 - R 300 U<sub>e</sub> = 125 V, I<sub>e</sub> = 0,22 A U<sub>e</sub> = 250 V, I<sub>e</sub> = 0,1 A</p>	
▶ Faston size	6,35 mm or 2 x 2,8 mm		



# Technical characteristics

## ▶ CONTACT BLOCKS

Pin-style connection (for PCB)	Data	Standards	
▶ Rated insulation voltage	250 V AC 250 V AC	IEC/EN60947-1 UL 508	
▶ NC contacts	Positive opening	IEC/EN 60947-5-1	
▶ Rated impulse withstanding voltage Uimp Pollution degree	4 kV 3		
▶ Conventional thermal current in free air conditions	AC 15: 5 A DC 13: 1 A	IEC 60947-5-1	
▶ Electrical ratings	<b>Alternating current</b> AC 15 - B 300 Ue = 120 V, Ie = 3 A Ue = 240 V, Ie = 1,5 A	<b>Direct current</b> DC13 - R 300 Ue = 125 V, Ie = 0,22 A Ue = 250 V, Ie = 0,1 A	IEC 60947-5-1 IEC 60947-5-4
	<b>Minimum current of use</b> - standard blocks Ue = 24 V DC and Ie = 5 mA Failure rate < 10 <sup>-8</sup>	- golden contacts Ue = 5 V DC and Ie = 1 mA Failure rate < 10 <sup>-8</sup>	
▶ Electrical operating life	<b>1 million cycles for:</b> - AC15 - B 300 Ue = 120 V, Ie = 3 A Ue = 240 V, Ie = 1,5 A	- DC13 - R 300 Ue = 125 V, Ie = 0,22 A Ue = 250 V, Ie = 0,1 A	
▶ Pin diameter	∅ 1 mm		

## ▶ LED BLOCKS FOR ILLUMINATED HEADS AND ONE PIECE LED PILOT LIGHTS

Characteristics	Data	Standards
▶ Rated insulation voltage	300 V	IEC/EN 60947-5-1
▶ Rated impulse voltage Uimp Pollution degree	4 kV (with filter block see p. 64) 3	IEC/EN 60947-5-1
▶ Operating voltage	12 to 24 V AC/DC 48 V AC/DC (for LED block) 130 V AC 230 V AC	
▶ Frequency	50 or 60 Hz	
▶ Lifetime at rated supply voltage	Red and yellow: 100 000 hours at 25 °C Other colours: 50 000 hours at 25 °C	
▶ Consumption of LED blocks	Voltage: - 24 V: 25 mA ± 20% - 48 V: 15 mA ± 5% - 130 V: 20 mA ± 10% - 230 V: 16 mA ± 30%	

# Technical characteristics

## ▶ ONE PIECE PILOT LIGHT BA9S

Characteristics	Data	Standards
▶ Rated insulation voltage	400 V	IEC 60947-5-1
▶ Rated impulse withstand voltage Uimp	4 kV	IEC/EN 60947-1
▶ Bulb rating	400 V max. - 2,6 W max. 240 V max. - 2,6 W max.	IEC 60947-5-1 UL 508

## ▶ HEADS

Characteristics	Data	Standards
▶ Mechanical endurance (in million cycles)	Spring return: 5 Push-push: 0,5 Selector switches: 0,3 Mushroom head maintained function EN 418: 0,10 Mushroom head maintained function: 0,15	
▶ Activation force in N	Spring return + NO: 6,5 Spring return + NC: 4,5 Additional NO contact: 4,5 Additional NC contact: 3,0 Push-pull mushroom head + NO + NC: 27 Push-turn mushroom head + NO + NC: 22 Push-pull mushroom head EN 418 + NO + NC: 37 Push-turn mushroom head EN 418 + NO + NC: 60	
▶ Activation force in Nm	Selector switch + NO: 0,04 Additional NO contact: 0,03	

## ▶ EMERGENCY STOP ACTUATORS - EN 418:

For equipment subject to Machine Security Directive CE 98/37 and EN60204 standard.

BACO emergency stop switches EN418 and contact blocks meet the requirements of the European Machine Directive EN 418 and EN60947-5-5 specification.

Our E-stops provide the "fool-proof" or "tease-proof" emergency stop switch feature - described below, that latches in the emergency stop command and then switches the contact state to open the circuit and shut down the equipment.

"After the emergency stop command has been generated during actuation of the emergency stop device, the command shall be maintained by engagement (latching-in) of the actuating means. The emergency stop command shall be maintained until the emergency stop device is reset (disengaged). It shall not be possible for the emergency stop device to engage without generating the stop command."


Simply stated, this directive indicates that the latching mechanism of the switch is activated when the actuator is pushed to a certain point. The switch will continue to remain in this latched position until manually reset by twisting to release.

# Diagrams

## MECHANICAL OPERATION

For 3 position selector switches

Handle position  
(front side view)



Contacts block actuation  
(back view)



Back side view

Non operated block


Operated block




## MECHANICAL OPERATION

For Joysticks

2 positions




4 positions




## PUSH-TO-TEST LED PILOT LIGHT DIAGRAMS


Lamp-testing module with 1 diode (33ET) for direct supply 24 V and 48 V



Lamp-testing module with 2 diodes (33ETT) for direct supply 24 V and 48 V



Lamp-testing assembly for direct supply 130 V and 240 V  
(Consult us - see page 79)



## PRINTED CIRCUIT BOARD MOUNTING

