

CERTIFICATE OF COMPLIANCE

Certificate Number A-E164353
Report Reference E39281-20180108
Issue Date 2020-APRIL-16

Issued to: Schneider Electric Industries S A, DBA Telemecanique
8001 Knightdale Blvd, Knightdale NC 27545

**This certificate confirms that
representative samples of** AUXILIARY DEVICES
See next page for models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 508 STANDARD FOR INDUSTRIAL CONTROL
EQUIPMEN
CSA C22.2 NO. 14-18 INDUSTRIAL CONTROL
EQUIPMENT

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number A-E164353
Report Reference E39281-20180108
Issue Date 2020-APRIL-16

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Flush Push button and pilot light assemblies (22 mm line) Cat. No. XB4F or XB5F, followed by A, D, G, H, J, K, L, V, or W, followed by two, three, four, or five numbers and / or letter suffixes, C0, C1 or CUST.

Operators, Cat. No. ZB4F or ZB5F, followed by A, D, G, H, J, or L, followed by 0, 1, 2, 3, 4 5, 6, 7, 8 or 9, followed by one, two, three or four alphanumeric digits, C0, C1 or CUST.

Pilot light heads, Cat. No. ZB4FV0 or ZB5FV0 followed by two numbers,

May be followed by, C0, C1 or CUST.

Illuminated operators, Cat. No. ZB4F or ZB5F, followed by W, H, or K followed by one, two, three, or four alphanumeric digits, C0, C1 or CUST.

Accessories: Legend holders, anti-rotation plate, caps, Cat. No. ZBA, ZBY, ZBZ, ZB4FBZ, ZB5FAZ, ZB4FS, ZB5FS followed by any alphanumeric digits.

Metal ring for flush mounting on 30.5 mm diameter holes, up to 4-way cut-outs, type ZB4FBZ014



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

