




RS232 to RS422/RS485 Converter Adapter (4-Pack)

TI-S400 (v1.0R)


- Includes four RS232 to RS422/RS485 converter adapters
- Convert an RS232 port to an RS422/RS485 terminal block
- Designed for use with the TI-M12 and TI-M42 industrial modbus gateways

TRENDnet's RS232 to RS422/RS485 Converter Adapter (4-Pack), model TI-S400, is designed for use with our TI-M12 and TI-M42 industrial modbus gateways.



RS232 to RS422/RS485 Converter Adapter

Quickly and easily convert an RS232 port into an RS422/RS485 terminal block.



Compatibility

Designed for use with the TI-M12 and TI-M42 industrial modbus gateways.

FEATURES



RS232 to RS422/RS485 Converter Adapter

Convert an RS232 port to an RS422/RS485 terminal block with this serial to terminal block adapter



Compatibility

This DB9 terminal block adapter is designed for use with TRENDnet's TI-M12 and TI-M42 industrial modbus gateways

SPECIFICATIONS

Interface (Single unit)

- 1 x DB9 Female RS-232 to RS-422/RS485
- 1 x Terminal block

Terminal Block

- Redundant power inputs, 5-pin
- Wire range: 26-14AWG
- Solid wire (AWG): 26-14AWG
- Stranded wire (AWG): 26-14AWG
- Torque: 0.4Nm (3.6 Lb.-In)
- Wire strip length: 6-7mm

Operating Temperature

- 0° – 40° C (32° – 104° F)

Dimensions (Single unit)

- 30 x 33 x 15mm (1.2 x 1.3 x 0.6 in.)

Weight (Single unit)

- 16g (0.5 oz.)

Warranty

- 1 year

Package Contents

- 4 x TI-S100