SOLISTRAND* Pressure Type Wire Connectors, Terminals and Splices (Use Type "W" Tooling)

408-2049
25 JAN 24 Rev P
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS	WIRE SIZE RANGE AND TYPE	424C LISTED	LR 7189 CERTIFIED
	22-16 AWG SOLID OR STRANDED	22-16 AWG SOLID OR STRANDED	22-16 AWG SOLID OR STRANDED
	16-14 AWG SOLID OR STRANDED	16-14 AWG SOLID OR STRANDED	16-14 AWG SOLID OR STRANDED
	12-10 AWG SOLID OR STRANDED	12-10 AWG STRANDED	12-10 AWG SOLID OR STRANDED
	8 AWG-600 MCM SOLID OR STRANDED	8 AWG-600 MCM STRANDED	8-4/0 AWG SOLID OR STRANDED

424C LISTED

SOLISTRAND* Catalog numbers	1KV Cable Size	No. of Strands/ Strand Diameter-In.
31808	8 AWG Cu.	168/0.0100
321598	6 AWG Cu.	61/0.0201
31811	4 AWG Cu.	133/0.0177
320383, 321600, 323291	2 AWG Cu.	259/0.0160
321866	1 AWG Cu.	224/0.0199
321866	1/0 AWG Cu.	266/0.0199
321870	2/0 AWG Cu.	323/0.0201
321271	4/0 AWG Cu.	532/0.0199
322252, 322254	262 kcmil Cu.	646/0.0199
322257, 322259	373 kcmil Cu.	925/0.0199
322262, 322264	444 kcmil Cu	1110/0.0199
322267	535 kcmil Cu	1332/0.0199

SOLISTRAND* Catalog numbers	7.5 KV Cable Size	No. of Strands/ Strand Gage, Diameter-In.
31808	8 AWG Cu.	84/27 (0.0142)
321598	6 AWG Cu.	84/25 (0.0179)
31811	4 AWG Cu.	105/24 (0.0201)
320383, 321600, 323291	2 AWG Cu.	163/24 (0.0201)
321866	1/0 AWG Cu.	262/24 (0.0201)
321870	2/0 AWG Cu.	504/26 (0.0159)
321271	4/0 AWG Cu.	805/26 (0.0159)

SOLISTRAND* Catalog numbers	15 KV Cable Size	No. of Strands/ Strand Diameter-In.
320383, 321600, 323291	2 AWG Cu.	259/0.0159
321866	1/0 AWG Cu.	414/0.0159
321870	2/0 AWG Cu.	522/0.0159
321271	4/0 AWG Cu.	829/0.0159

SOLISTRAND* Catalog numbers	Cable Size	No. of Strands/ Strand Gauge, Diameter-In.
1958536-1	4 AWG UL TYPE 1283 Cu	133/27 (0.0142)
1958536-1	4 AWG UL AWM 10070/ CSA AWM Tinned Copper	4361/40 (0.0031)

NOTE: PN 33457, UL Listed, 12-10 AWG Solid or Stranded Copper wire.
NOTE: P/N's 324001 & 8-324001-0, UL Listed / CSA Certified, 22-20 AWG Solid or Stranded wire.
NOTE: PN 184269-1, CSA Certified only, 16-14 AWG Solid or Stranded Copper wire.
NOTE: Terminals and splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).
DANGER! DO NOT use with aluminum wire; otherwise, equipment failure may result causing serious injury or death.
DANGER! NE PAS utiliser avec des conducteurs en aluminium ; sinon, une défaillance de l'équipement peut entraîner des blessures graves ou la mort.

© 2023 TE Connectivity Ltd. family of companies.
All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For Regional Customer Service, visit our website at **www.te.com**

* Trademark TE Connectivity, TE connectivity (logo) and Every Connection Counts are trademarks.

SOLISTRAND* Pressure Type Wire Connectors, Terminals and Splices (Use Type "W" Tooling)

408-2049
25 JAN 24 Rev P
CU

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS	WIRE SIZE RANGE AND TYPE	424C LISTED	LR 7189 CERTIFIED
	22-16 AWG SOLID OR STRANDED	22-16 AWG SOLID OR STRANDED	22-16 AWG SOLID OR STRANDED
	16-14 AWG SOLID OR STRANDED	16-14 AWG SOLID OR STRANDED	16-14 AWG SOLID OR STRANDED
	12-10 AWG SOLID OR STRANDED	12-10 AWG STRANDED	12-10 AWG SOLID OR STRANDED
	8 AWG-600 MCM SOLID OR STRANDED	8 AWG-600 MCM STRANDED	8-4/0 AWG SOLID OR STRANDED

424C LISTED

SOLISTRAND* Catalog numbers	1KV Cable Size	No. of Strands/ Strand Diameter-In.
31808	8 AWG Cu.	168/0.0100
321598	6 AWG Cu.	61/0.0201
31811	4 AWG Cu.	133/0.0177
320383, 321600, 323291	2 AWG Cu.	259/0.0160
321866	1 AWG Cu.	224/0.0199
321866	1/0 AWG Cu.	266/0.0199
321870	2/0 AWG Cu.	323/0.0201
321271	4/0 AWG Cu.	532/0.0199
322252, 322254	262 kcmil Cu.	646/0.0199
322257, 322259	373 kcmil Cu.	925/0.0199
322262, 322264	444 kcmil Cu	1110/0.0199
322267	535 kcmil Cu	1332/0.0199

SOLISTRAND* Catalog numbers	7.5 KV Cable Size	No. of Strands/ Strand Gage, Diameter-In.
31808	8 AWG Cu.	84/27 (0.0142)
321598	6 AWG Cu.	84/25 (0.0179)
31811	4 AWG Cu.	105/24 (0.0201)
320383, 321600, 323291	2 AWG Cu.	163/24 (0.0201)
321866	1/0 AWG Cu.	262/24 (0.0201)
321870	2/0 AWG Cu.	504/26 (0.0159)
321271	4/0 AWG Cu.	805/26 (0.0159)

SOLISTRAND* Catalog numbers	15 KV Cable Size	No. of Strands/ Strand Diameter-In.
320383, 321600, 323291	2 AWG Cu.	259/0.0159
321866	1/0 AWG Cu.	414/0.0159
321870	2/0 AWG Cu.	522/0.0159
321271	4/0 AWG Cu.	829/0.0159

SOLISTRAND* Catalog numbers	Cable Size	No. of Strands/ Strand Gauge, Diameter-In.
1958536-1	4 AWG UL TYPE 1283 Cu	133/27 (0.0142)
1958536-1	4 AWG UL AWM 10070/ CSA AWM Tinned Copper	4361/40 (0.0031)

NOTE: PN 33457, UL Listed, 12-10 AWG Solid or Stranded Copper wire.
NOTE: P/N's 324001 & 8-324001-0, UL Listed / CSA Certified, 22-20 AWG Solid or Stranded wire.
NOTE: PN 184269-1, CSA Certified only, 16-14 AWG Solid or Stranded Copper wire.
NOTE: Terminals and splices used with wire sizes 22-16 AWG are stamped with 22-18 in accordance with SAE-AS7928 (formerly MIL-T-7928).
DANGER! DO NOT use with aluminum wire; otherwise, equipment failure may result causing serious injury or death.
DANGER! NE PAS utiliser avec des conducteurs en aluminium ; sinon, une défaillance de l'équipement peut entraîner des blessures graves ou la mort.

© 2023 TE Connectivity Ltd. family of companies.
All Rights Reserved

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752

For Regional Customer Service, visit our website at **www.te.com**

* Trademark TE Connectivity, TE connectivity (logo) and Every Connection Counts are trademarks.