

# Fuse - SI FORM C 4 A DIN 72581 - 0913731

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Flat-type plug-in fuse, type C, color code: pink, nominal current: 4 A

The figure shows a version of the article

## Product Features

- Fuse holder for flat-type fuses with a maximum nominal voltage of 32 V
- With snap-in foot for secure pre-assembly on the PCB

## Key commercial data

<b>package_quantity</b>	50
<b>GTIN</b>	4017918008680

## Technical data

### General

<b>Color</b>	Pink
<b>Inflammability class according to UL 94</b>	V0

### General

<b>Fuse</b>	C
<b>Nominal current I<sub>N</sub></b>	4 A
<b>Nominal voltage U<sub>N</sub></b>	24 V

### Dimensions

<b>Width</b>	5 mm
<b>Length</b>	19 mm
<b>Height NS 35/7,5</b>	13 mm

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	27141199
<b>eCl@ss 4.1</b>	27141199
<b>eCl@ss 5.0</b>	[NO ASSET AVAILABLE: TXB,7175181,P]
<b>eCl@ss 5.1</b>	[NO ASSET AVAILABLE: TXB,7175182,P]
<b>eCl@ss 6.0</b>	27142001

# Fuse - SI FORM C 4 A DIN 72581 - 0913731

## classifications

### eCl@ss

eCl@ss 7.0	27142008
eCl@ss 8.0	27142008

### ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC002298
ETIM 4.0	EC002298
ETIM 5.0	EC002298

### UNSPSC

UNSPSC 6.01	30211813
UNSPSC 7.0901	39121410
UNSPSC 11	39121412
UNSPSC 12.01	39121412
UNSPSC 13.2	39121412

## approvals

---

GOST /

---

### Approval details



## Drawings

© Phoenix Contact 2013 - all rights reserved  
<http://www.phoenixcontact.com>