

## **VOLTCRAFT**®

#### **VOLTCRAFT® - TOP PERFORMANCE IN EVERY WAY**

"For more than 25 years, our product range has been dynamically adapting to the constant changes in the industry. We commit to offering first-class quality to our customers while delivering an excellent cost-performance ratio. This philosophy remains the cornerstone of Voltcraft's success."

# BS-30XHR ENDOSKOP

CE

VERSION 09/14

Nº 1086336

The endoscope is a visual aid for troubleshooting or inspection of voltage-free systems and installations. The camera image is displayed on the built-in monitor. The light on the camera head can be adjusted. The removable gooseneck camera is waterproof (IP67) and suited for use in watery liquids (no acidic or basic solutions). The main unit may not be exposed to or submerged in moisture. Power supply is via four AA batteries (not included). Operation in potentially explosive areas and/or use on persons or animals is not permitted.

### HIGHLIGHTS

6.9 cm TFT monitor with 960 x 240 pixels //

Waterproof mini camera (IP67) with 4 dimmable white LEDs //

Removable flexible gooseneck //

Rotating image //

Zoom function //

Adjustable background light //



#### **TECHNICAL DATA**

4 75 14 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
4 x 1.5 V battery type AA (not included)
6.9 cm (2.7")
960 x 240 pixels (monitor)
640 x 480 pixels (camera)
4 white LEDs
automatic
automatic
54º
≥6 cm
0 to +45 ºC, 15 – 85 % RH
-10 to +50 ºC, 15 – 85 % RH
min. 45 mm
88 cm ±2 cm
6.5 mm
8 mm
86 x 219 x 53 mm
approx. 330 g

#### **PACKAGE CONTENT**

Endoscope // Gooseneck camera // 3 x attachements (magnet, hook, mirror) // Storage case // Operating instructions

All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval by the editor. Reprinting, also in part, is prohibited. This data sheet represents the technical status at the time of printing.