

SAFETY DATA SHEET of Absima Paintz (Polycarbonate Color Spray)

Revision date : Wednesday, June 18, 2014

1 Identification of the substance/mixture and of the company/undertaking :

1.1 Product identifier:

RC Car (Aerosol)

1.2 Relevant identified uses of the substance or mixture and uses advised against/

Concentration in use : /

1.3 Details of the supplier of the safety data sheet

Absima GmbH

Gibitzenhofstr. 127A RG

90443 Nürnberg

Phone: 0049 (0) 911 65084130 Fax: 0049 (0) 911 65084140
E-mail: info@absima.com Website: www.absima.com

1.4 Emergency telephone number

0044 (171) 635 91 91

2 Hazards identification:

2.1 Classification of the substance or mixture

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008

EUH066 H222 Flam. Aerosol 1 H229 H319 Eye Irrit. 2 H336 STOT SE 3

Classification of the substance or mixture in accordance with regulation 67/548/EC :

R12: Extremely flammable R36: Irritant R66 R67

2.2 Label elements:

Symbols:



Signal word:

Danger

Risk Phrases:

EUH066: Repeated exposure may cause skin dryness or cracking.

H222 Flam. Aerosol 1: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H319 Eye Irrit. 2: Causes serious eye irritation.

H336 STOT SE 3: May cause drowsiness or dizziness.

Safety phrases:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251: Pressurized container: Do not pierce or burn, even after use.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P410+P412: Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.

Contains:

none

2.3 Other hazards:

none

3 Composition/information on ingredients:

Acetone	> 30%	CAS number:	67-64-1	
		EINECS:	200-662-2	
		REACH Registration number:	01-2119471330-49	
		CLP Classification:	EUH066 H225 Flam. Liq. 2 H319 Eye Irrit. 2 H336 STOT SE 3	
		R-Phrases:	R11 R36 R66 R67	
Dimethylether	> 30%	CAS number:	115-10-6	
		EINECS:	204-065-8	
		REACH Registration number:	01-2119472128-37	
		CLP Classification:	H220 Flam. Gas 1	
		R-Phrases:	R12	
2-methoxy-1-methylethyl acetate	< 5%	CAS number:	108-65-6	
		EINECS:	203-603-9	
		REACH Registration number:	01-2119475791-29	
		CLP Classification:	H226 Flam. Liq. 3	
		R-Phrases:	R10	

n-Butylacetate	5% - 15%	CAS number:	123-86-4	
		EINECS:	204-658-1 01-2119485493-29	
		REACH Registration number:		
		CLP Classification:	EUH066 H226 Flam. Liq. 3 H336 STOT SE 3	
		R-Phrases:	R10 R66 R67	
Methyl ethyl ketone	< 5%	CAS number:	78-93-3	
		EINECS:	201-159-0	
		REACH Registration number:	01-2119457290-43	
		CLP Classification:	EUH066 H225 Flam. Liq. 2 H319 Eye Irrit. 2 H336 STOT SE 3	
		R-Phrases:	R11 R36 R66 R67	

For the full text of the H & R phrases mentioned in this section, see section 16.

4 First aid measures:

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact: remove contaminated clothing, rinse with plenty of water, if necessary seek medical

attention.

Eye contact: first prolonged rinsing with water (contact lenses to be removed if this is easily done)

then take to physician.

Ingestion: rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: let sit upright, fresh air, rest and take to hospital.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: is absorbed, dry skin, redness **Eye contact:** redness, pain, bad looking

Ingestion: diarrhoea, headache, abdominal cramps, sleepiness, vomiting

Inhalation: sore throat, cough, shortness of breath, headache

4.3 Indication of any immediate medical attention and special treatment needed:

none

5 Fire-fighting measures:

5.1 Extinguishing media:

CO2, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

none

5.3 Advice for fire-fighters:

6 Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up windRemove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

remove by using absorbent material.

6.4 Reference to other sections:

for further information check sections 8 & 13.

7 Handling and storage:

7.1 Precautions for safe handling:

handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

/

8 Exposure controls/personal protection:

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

Dimethylether 1,920 mg/m³, Acetone 1,210 mg/m³, n-Butylacetate 723 mg/m³, Methyl ethyl ketone 600 mg/m³, 2-methoxy-1-methylethyl acetate 275 mg/m³

8.2 Exposure controls:

Inhalation protection:	if necessary, use an air-purifying face mask in case of respiratory hazards.	
Skin protection:	handling with butyl-gloves. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	

Other protection:

impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.



9 Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Melting point/melting range:

Boiling point/Boiling range: -24 °C — 118 °C

pH: /
pH 1% diluted in water: /

Vapour pressure/20°C,: 533 320 Pa
Vapour density: not applicable
Relative density, 20°C: 0.800 kg/l
Appearance/20°C: liquid
Flash point: -18 °C

Flammability (solid, gas): not applicable

Auto-ignition temperature: $350 \,^{\circ}\text{C}$ Upper flammability or explosive $27.000 \,^{\circ}$

limit, (Vol %):

Lower flammability or explosive

limit, (Vol %):

1.300 %

Explosive properties: not applicable

Oxidising properties: not applicable

Decomposition temperature:

Solubility in water: not soluble

Partition coefficient: n- not applicable

octanol/water:

Odour: characteristic
Odour threshold: not applicable
Dynamic viscosity, 20°C: 1 mPa.s
Kinematic viscosity, 20°C: 1 mm²/s
Evaporation rate (n-BuAc = 1): 5.600

9.2 Other information:

Volatile organic component (VOC): 92.61 %
Volatile organic component (VOC): 714.388 g/l

10 Stability and reactivity:

10.1 Reactivity:

stable under normal conditions.

10.2 Chemical stability:

extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

10.4 Conditions to avoid:

protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

keep away from sources of ignition

10.6 Hazardous decomposition products:

doesn't decompose with normal use

11 Toxicological information:

11.1 Information on toxicological effects:

About the preparation itself: not applicable under actual EEC guidelines for preparations.

General information: See ingredients under section 3

Calculated acute toxicity, LD50 oral

rat:

Calculated acute toxicity, LD50

dermal rat:

12 Ecological information:

12.1 Toxicity:

not applicable under actual EEC guidelines for preparations.

12.2 Persistence and degradability:

not applicable under actual EEC guidelines for preparations.

12.3 Bioaccumulative potential:

not applicable under actual EEC guidelines for preparations.

12.4 Mobility in soil:

Water hazard class, WGK:

Solubility in water: not soluble

12.5 Results of PBT and vPvB assessment:

not applicable under actual EEC guidelines for preparations.

12.6 Other adverse effects:

not applicable under actual EEC guidelines for preparations.

13 Disposal considerations:

13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

14 Transport information:

14.1 UN number:

1950

14.2 UN proper shipping name:

UN 1950 Aerosols, flammable, 5F, (D)

14.3 Transport hazard class(es):

Class(es): 5F

Identification number of the

hazard:

not applicable

14.4 Packing group:

not applicable

14.5 Environmental hazards:

not dangerous to the environment

14.6 Special precautions for user:

Hazard characteristics: Risk of fire. Risk of explosion. Containments may explode when heated.

Additional guidance: Take cover. Keep out of low areas. Prevent leaking substances from running into the

aquatic environment or the sewage system.



15 Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK: 1

Volatile organic component (VOC): 92.614 %
Volatile organic component (VOC): 714.388 g/l
Composition by regulation (EC) none

648/2004:

15.2 Chemical Safety Assessment:

No data available

16 Other information:

Legend to abbreviations used in the safety data sheet:

DPD: Dangerous Preparations Directive

WGK 1: slightly hazardous for water

WGK: Water hazard class
WGK 2: hazardous for water

ADR: Accord européen relatif au transport international des marchandises Dangereuses

par Route

CLP: Classification, Labelling and Packaging of chemicals

WGK3: extremely hazardous for water

EINECS: European INventory of Existing Commercial chemical Substances

CAS: Chemical Abstracts Service

Nr.: number

PTB: persistent, toxic, bioaccumulative

zPzB: very persistent and very bioaccumulative substances

TLV: Threshold Limit Value

Legend to the R & H Phrases used in the safety data sheet:

R10: Flammable. R11: Highly flammable. R12: Extremely flammable. R36: Irritating to eyes. R66: Repeated exposure may cause skin dryness or cracking R67: Vapours may cause drowsiness and dizziness

EUH066: Repeated exposure may cause skin dryness or cracking. H220 Flam. Gas 1: Extremely flammable gas. H222 Flam. Aerosol 1: Extremely flammable aerosol. H225 Flam. Liq. 2: Highly flammable liquid and vapour. H226 Flam. Liq. 3: Flammable liquid and vapour. H229: Pressurised container: May burst if heated. H319 Eye Irrit. 2: Causes serious eye irritation. H336 STOT SE 3: May cause drowsiness or dizziness.

Reason of revision, changes of following items:

not applicable

MSDS reference number:

ECM-103015,01

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 453/2010. Classification has been calculated in accordance with the European directive 67/548/EWG, 1999/45/EC and regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.