

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** LEDVANCE

**Supplier's address:** LEDVANCE GmbH, Parkring 33, Garching, Germany

**Model identifier:** AC33865

## Type of light source:

|   |      |                                 |      |
|---|------|---------------------------------|------|
| Lighting technology used:                           | LED  | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | G13  |                                 |      |
| Mains or non-mains:                                 | NMLS | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No   | Envelope:                       | -    |
| High luminance light source:                        | No   |                                 |      |
| Anti-glare shield:                                  | No   | Dimmable:                       | No   |

## Product parameters

| Parameter  | Value                  | Parameter  | Value                  |       |
|--|------------------------|--|------------------------|-------|
| <b>General product parameters:</b>   |                        |  |                        |       |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 26                     | Energy efficiency class  | D                      |       |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 3 700 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000                  |       |
| On-mode power ( $P_{on}$ ), expressed in W   | 23,0                   | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00                   |       |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                      | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 83                     |       |
| Outer dimensions without   | Height                 | Spectral power distribution in the   | See image in last page |       |
|  | Width                  |  |                        | 1 513 |
|  | Depth                  |  |                        | 27    |
|  |                        | 27   |                        |       |

|   |      |                                      |       |
|---|------|--------------------------------------|-------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) |      | range 250 nm to 800 nm, at full-load |       |
| Claim of equivalent power <sup>(a)</sup>  | -    | If yes, equivalent power (W)         | -     |
|   |      | Chromaticity coordinates (x and y)   | 0,381 |
| <b>Parameters for LED and OLED light sources:</b>   |      |                                      |       |
| R9 colour rendering index value   | 0    | Survival factor                      | 0,90  |
| the lumen maintenance factor  | 0,70 |                                      |       |

(a): not applicable;

(b): not applicable;

