

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 17/02/2025 Revision date: 27/08/2024 Supersedes version of: 25/04/2024 Version: 1.4

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Galva Brite

UFI : 786X-T8US-F009-UCWN

Product code : BDS002664AE Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Main use category : Professional use

Use of the substance/mixture : Paints

#### 1.3. Details of the supplier of the safety data sheet

#### Supplier

CRC Industries Europe B.V.

Touwslagerstraat 1

9240 Zele

Belgium

T +32(0)52/45.60.11, F +32(0)52/45.00.34

hse@crcind.com, www.crcind.com

#### 1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11

Office hours: 9-17h CET

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, H336

Narcosis

Aspiration hazard, Category 1 H304 Hazardous to the aquatic environment – Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS07

GHS09

Signal word (CLP) : Da

Contains : Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics;2-methoxy-1-

methylethyl acetate;n-butyl acetate;ethyl acetate

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P280 - Wear protective gloves/eye protection.

P501 - Dispose of contents/container to a hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

EUH066 - Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

**EUH-statements** 

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128- 37	75 – 100	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258- 33	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066
ethyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5 REACH-no: 01-2119475103-46	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
2-methoxy-1-methylethyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-	1 – 5	Flam. Liq. 3, H226 STOT SE 3, H336
n-butyl acetate substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	1 – 5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
zinc oxide substance with national workplace exposure limit(s) (BE)	CAS-No.: 1314-13-2 EC-No.: 215-222-5 EC Index-No.: 030-013-00-7 REACH-no: 01-2119463881- 32	< 2,5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Calcium bis(2-ethylhexanoate)	CAS-No.: 136-51-6 EC-No.: 205-249-0 REACH-no: 01-2119978297- 19	< 0,3	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Dam. 1, H318 Repr. 1B, H360D

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop,

get medical attention.

First-aid measures after skin contact : Wash skin with plenty of water. Seek medical attention if irritation develops.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Risk of lung oedema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated.

Hazardous decomposition products in case of fire : During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Use standard

firefighting procedures and consider the hazards of other involved materials.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it

with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to

remove residual contamination.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For disposal of contaminated materials refer to section 13: "Disposal considerations".

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good

industrial hygiene and safety procedures.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked

up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated

place. Keep cool. Keep container closed when not in use

### 7.3. Specific end use(s)

No additional information available

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### National occupational exposure and biological limit values

# zinc oxide (1314-13-2) Belgium - Occupational Exposure Limits

Local name Zinc (oxyde de) (fraction alvéolaire) # Zinkoxide (inadembare fractie)

27/08/2024 (Revision date) BE - en 4/19

# Safety Data Sheet

zinc oxide (1314-13-2)	
OEL TWA	2 mg/m³
OEL STEL	10 mg/m³
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
2-methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m³
	50 ppm
IOEL STEL	550 mg/m³
	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	Acétate de 2-(1-méthoxy)propyle # 2-(1-Methoxy)propylacetaat
OEL TWA	275 mg/m³
	50 ppm
OEL STEL	550 mg/m³
	100 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m³
	50 ppm
IOEL STEL	723 mg/m³
	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
Belgium - Occupational Exposure Limits	
Local name	Acétate de n-butyle # n-Butylacetaat
OEL TWA	238 mg/m³
	50 ppm
OEL STEL	as Fr
OEL STEL	712 mg/m³
OEL STEL	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl acetate (141-78-6)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Ethyl acetate	
IOEL TWA	734 mg/m³	
	200 ppm	
IOEL STEL	1468 mg/m³	
	400 ppm	
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164	
Belgium - Occupational Exposure Limits		
Local name	Acétate d'éthyle # Ethylacetaat	
OEL TWA	734 mg/m³	
	200 ppm	
OEL STEL	1468 mg/m³	
	400 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	
dimethyl ether (115-10-6)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Dimethylether	
IOEL TWA	1920 mg/m³	
	1000 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Belgium - Occupational Exposure Limits		
Local name	Oxyde de diméthyle # Dimethylether	
OEL TWA	1920 mg/m³	
	1000 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023	

### **DNEL and PNEC**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	208 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	871 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	125 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	185 mg/m³	
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day	
zinc oxide (1314-13-2)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	83 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	5 mg/m³	

# Safety Data Sheet

zinc oxide (1314-13-2)		
Long-term - local effects, inhalation	0,5 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0,83 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,5 mg/m³	
Long-term - systemic effects, dermal	83 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	20,6 μg/l	
PNEC aqua (marine water)	6,1 µg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	117,8 mg/kg dwt	
PNEC sediment (marine water)	56,5 mg/kg dwt	
PNEC (Soil)		
PNEC soil	35,6 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 µg/l	
2-methoxy-1-methylethyl acetate (108-65-6)		
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	550 mg/m³	
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	275 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, oral	500 mg/kg bodyweight/day	
Long-term - systemic effects,oral	36 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	33 mg/m³	
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day	
Long-term - local effects, inhalation	33 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0,635 mg/l	
PNEC aqua (marine water)	0,0635 mg/l	
PNEC aqua (intermittent, freshwater)	6,35 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3,29 mg/kg dwt	
PNEC sediment (marine water)	0,329 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,29 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	

# Safety Data Sheet

n-butyl acetate (123-86-4)	
PNEC (Water)	
PNEC aqua (freshwater)	0,18 mg/l
PNEC aqua (marine water)	0,018 mg/l
PNEC aqua (intermittent, freshwater)	0,36 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0,981 mg/kg dwt
PNEC sediment (marine water)	0,0981 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,0903 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35,6 mg/l
ethyl acetate (141-78-6)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1468 mg/m³
Acute - local effects, inhalation	1468 mg/m³
Long-term - systemic effects, dermal	63 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	734 mg/m³
Long-term - local effects, inhalation	734 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	734 mg/m³
Acute - local effects, inhalation	734 mg/m³
Long-term - systemic effects,oral	4,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	367 mg/m³
Long-term - systemic effects, dermal	37 mg/kg bodyweight/day
Long-term - local effects, inhalation	367 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	0,24 mg/l
PNEC aqua (marine water)	0,024 mg/l
PNEC aqua (intermittent, freshwater)	1,65 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	1,15 mg/kg dwt
PNEC sediment (marine water)	0,115 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,148 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	0,2 g/kg food
PNEC (STP)	
PNEC sewage treatment plant	650 mg/l

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

dimethyl ether (445 40 C)		
dimethyl ether (115-10-6)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, inhalation	1894 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects, inhalation	471 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0,155 mg/l	
PNEC aqua (marine water)	0,016 mg/l	
PNEC aqua (intermittent, freshwater)	1549 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0,681 mg/kg dwt	
PNEC sediment (marine water)	0,069 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0,045 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	160 mg/l	

### 8.2. Exposure controls

#### Appropriate engineering controls

#### Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Personal protection equipment

### Personal protective equipment symbol(s):





### Eye and face protection

### Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

#### Skin protection

### Skin and body protection:

Wear suitable protective clothing

### Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

### **Respiratory protection**

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: A

#### Thermal hazards

### Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Boiling point

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **Environmental exposure controls**

#### **Environmental exposure controls:**

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Grey.

Appearance : DME propelled liquid.
Odour
Odour threshold : Characteristic.
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

: Not available

 Lower explosion limit
 : Not available

 Upper explosion limit
 : Not available

 Flash point
 : -4 °C (closed cup)

 Auto-ignition temperature
 : > 200 °C

 Decomposition temperature
 : Not available

Decomposition temperature

pH

Not available

Not applicable

Viscosity, kinematic

2 < 20,5 mm²/s at 40 °C

Solubility

Insoluble in water.

Partition coefficient n-octanol/water (Log Kow) : Not applicable
Vapour pressure : Not available
Vapour pressure at 50°C : Not available
Density : 0,985 g/cm³ at 20 °C
Relative density : 0,985 at 20 °C
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

#### 9.2. Other information

### Information with regard to physical hazard classes

% of flammable ingredients : ≤ 100 %

Other safety characteristics

VOC content : 675 g/l (Cat.II B(e) VOC max 840 g/L)

Additional information : For aerosols data for the product without propellant.

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal)  Acute toxicity (inhalation)	<ul> <li>Not classified (Based on available data, the classification criteria are not met)</li> <li>Not classified (Based on available data, the classification criteria are not met)</li> </ul>
Hydrocarbons, C9-C11, n-alkanes, is	soalkanes, cyclics, < 2% aromatics
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
zinc oxide (1314-13-2)	
LD50 oral rat	7950 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	2500 mg/l
2-methoxy-1-methylethyl acetate (10	08-65-6)
LD50 oral rat	> 5000 mg/kg
LD50 oral	8532 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight
LD50 dermal	> 5000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 10800 mg/l
Calcium bis(2-ethylhexanoate) (136-	51-6)
LD50 oral rat	2043 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
n-butyl acetate (123-86-4)	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	23,4 mg/l/4h
ethyl acetate (141-78-6)	
LD50 oral	4934 mg/kg bodyweight
LD50 dermal rabbit	> 20000 mg/kg bodyweight
dimethyl ether (115-10-6)	
LC50 Inhalation - Rat	308,5 mg/l/4h
LC50 Inhalation - Rat [ppm]	164000 ppm

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met) pH: Not applicable

# Safety Data Sheet

ccording to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878		
n-butyl acetate (123-86-4)		
рН	6,2	
Serious eye damage/irritation	Causes serious eye irritation. pH: Not applicable	
n-butyl acetate (123-86-4)		
рН	6,2	
Respiratory or skin sensitisation  Germ cell mutagenicity  Carcinogenicity  Reproductive toxicity  STOT-single exposure	Not classified (Based on available data, the classification criteria are not met)  Not classified (Based on available data, the classification criteria are not met)  Not classified (Based on available data, the classification criteria are not met)  Not classified (Based on available data, the classification criteria are not met)  May cause drowsiness or dizziness.	
Hydrocarbons, C9-C11, n-alkanes, isoalkane	s, cyclics, < 2% aromatics	
STOT-single exposure	May cause drowsiness or dizziness.	
2-methoxy-1-methylethyl acetate (108-65-6)		
STOT-single exposure	May cause drowsiness or dizziness.	
n-butyl acetate (123-86-4)		
STOT-single exposure	May cause drowsiness or dizziness.	
ethyl acetate (141-78-6)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure	Not classified (Based on available data, the classification criteria are not met)	
2-methoxy-1-methylethyl acetate (108-65-6)		
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight	
Calcium bis(2-ethylhexanoate) (136-51-6)		
NOAEL (subchronic, oral, animal/male, 90 days)	180 mg/kg bodyweight	
NOAEL (subchronic, oral, animal/female, 90 days)	205 mg/kg bodyweight	
n-butyl acetate (123-86-4)		
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight	
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight	
ethyl acetate (141-78-6)		
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight	
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Galva Brite		
Vaporizer	Aerosol	
Viscosity, kinematic	< 20,5 mm²/s at 40 °C	
Hydrocarbons, C9-C11, n-alkanes, isoalkane	s, cyclics, < 2% aromatics	
Viscosity, kinematic	1,33 mm²/s	
n-butyl acetate (123-86-4)		
Viscosity, kinematic	0,83 mm²/s	

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 11.2. Information on other hazards

#### **Endocrine disrupting properties**

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term

: Not classified (Based on available data, the classification criteria are not met)

(acute)

. Not classified (based off available data, the classification criteria are not

Hazardous to the aquatic environment, long-term (chronic)

: Toxic to aquatic life with long lasting effects.

chone)		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
LC50 - Fish [1]	> 1000 mg/l	
EC50 - Crustacea [1]	> 1000 mg/l	
EC50 - Other aquatic organisms [1]	> 1000 mg/l	
EC50 72h - Algae [1]	> 1000 mg/l	
2-methoxy-1-methylethyl acetate (108-65-6)		
LC50 - Fish [1]	> 100 mg/l	
EC50 - Crustacea [1]	> 500 mg/l	
EC50 - Other aquatic organisms [1]	408 mg/l	
EC50 - Other aquatic organisms [2]	> 1000 mg/l	
EC50 72h - Algae [1]	> 1000 mg/l	
NOEC (chronic)	≥ 100 mg/l	
NOEC chronic fish	47,5 mg/l	
Calcium bis(2-ethylhexanoate) (136-51-6)		
LC50 - Fish [1]	> 100 mg/l	
EC50 - Crustacea [1]	910 mg/l Daphnia magna (Water flea)	
EC50 72h - Algae [1]	500 mg/l	
NOEC (chronic)	18 mg/l 21 d	
n-butyl acetate (123-86-4)		
LC50 - Fish [1]	18 mg/l	
EC50 - Crustacea [1]	44 mg/l	
EC50 72h - Algae [1]	674,7 mg/l	
LOEC (chronic)	47,6 mg/l	
NOEC (chronic)	23,2 mg/l	
NOEC chronic algae	200 mg/l	
ethyl acetate (141-78-6)		
LC50 - Fish [1]	230 mg/l	

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethyl acetate (141-78-6)		
EC50 - Other aquatic organisms [1]	717 mg/l Daphnia magna (Water flea)	
NOEC (chronic)	2,4 mg/l 21 d	
dimethyl ether (115-10-6)		
LC50 - Fish [1]	> 4,1 g/l	
EC50 - Crustacea [1]	> 4,4 g/l Daphnia magna (Water flea)	
EC50 96h - Algae [1]	154917 mg/l	

### 12.2. Persistence and degradability

Ga	lva	<b>Brite</b>

Persistence and degradability Not established. No data is available on the degradability of this product.

0,07

#### 12.3. Bioaccumulative potential

Galva Brite		
Partition coefficient n-octanol/water (Log Kow)	Not applicable	
2-methoxy-1-methylethyl acetate (108-65-6)		
Partition coefficient n-octanol/water (Log Pow)	1,2	
n-butyl acetate (123-86-4)		
Partition coefficient n-octanol/water (Log Pow)	2,3	
ethyl acetate (141-78-6)		
Partition coefficient n-octanol/water (Log Pow)	0,7	
dimethyl ether (115-10-6)		

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

Partition coefficient n-octanol/water (Log Pow)

Galva Brite	
Results of PBT assessment	Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

#### 12.7. Other adverse effects

Galva Brite	
Other information	No other effects known
Global warming potential (GWP)	0.70 (Fluorinated greenhouse gases - (EC) No 2024/573)

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods

European List of Waste (LoW, EC 2000/532)

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
4.1. UN number or ID r	number			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
4.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
ransport document desci	ription			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2. ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard	class(es)			
2.1	2.1	2.1	2.1	2.1
**************************************	***************************************	<b>*</b>	**************************************	
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	zards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L
Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID) : 23

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

#### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU-Regulations**

#### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

#### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

#### VOC Directive (2004/42)

VOC content : 675 g/l (Cat.II B(e) VOC max 840 g/L)

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### **SECTION 16: Other information**

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration

# Safety Data Sheet

Abbreviations and acronyms:	
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 1B	Reproductive toxicity, Category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.