

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking· **1.1 Product identifier**· **Trade name** **REVELL EMAIL COLOR**
No. 92,93,94,95· **Article number:**

R3200-9192; R3200-9193;

R3200-9194; R3200-9195

Revell-No.:

32192; 32193; 32194; 32195

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**· **Sector of Use** SU21 Consumer uses: Private households / general public / consumers· **Product category** PC9a Coatings and paints, thinners, paint removers· **Process category** PROC10 Roller application or brushing· **Application of the substance / the mixture** toy lacquer· **1.3 Details of the supplier of the safety data sheet**· **Manufacturer/Supplier:**

Dreisol Coatings GmbH & Co.KG.

Industriestraße 4

D-32361 Pr. Oldendorf-Bad Holzhausen

Tel.: +49(0)5742-9300-0(Zentrale)

Fax : +49(0)5742-9300-49

E-Mail: mail@dreisol.de<http://www.dreisol.de>

Revell GmbH

Henschelstr. 20-30

D-32257 Bünde

Tel.: +49(0)5223-965-0

<http://www.revell.de>· **Informing department:**

department product safety

e-mail adress of competent person:

Tel.: +49(0)5742/9300-41

sdb@dreisol.de· **1.4 Emergency telephone number:** Poison Information Centre (GIZ-Nord): Tel.: +49(0)551-19240**SECTION 2: Hazards identification**· **2.1 Classification of the substance or mixture**· **Classification according to Regulation (EC) No 1272/2008**

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **2.2 Label elements**· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS09

· **Signal word** Warning

· **Hazard-determining components of labelling:**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics*
 1-methoxypropan-2-ol

· **Hazard statements**

H226 Flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P240 Ground and bond container and receiving equipment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.
 Contains N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide). May produce an allergic reaction.

· **Information pertaining to particular dangers for man and environment**

· **Additional information**

Child-resistant fastening not required (Annex II, Part 3.1 CLP)
 Tactile warning not required (Annex II, Part 3.2 CLP)

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:**

Paint mixture based on acryl-copolymer and/or pigment/extender with the following components.

· **Dangerous components:**

CAS: 1174522-20-3 EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics* ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ STOT SE 3, H336	25-50%
CAS: 7440-50-8 EINECS: 231-159-6 Reg.nr.: 01-2119480154-42	copper ⚠ Flam. Sol. 1, H228 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H302; Eye Irrit. 2, H319	20-25%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 2)

CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	7-10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxypropan-2-ol Flam. Liq. 3, H226 STOT SE 3, H336	7-10%
CAS: 7440-66-6 EINECS: 231-175-3 Reg.nr.: 01-2119467174-37	zinc powder -zinc dust (stabilized) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.5-1%
CAS: 123-26-2 EINECS: 204-613-6 Reg.nr.: 01-2119978265-26	N,N'-ethane-1,2-diylbis(12-hydroxyoctadecan-1-amide) Skin Sens. 1B, H317 Aquatic Chronic 3, H412	0.3-0.5%

Additional information

*) Benzene content is less than 0.1% (EINECS-No. 200-753-7). It is P. Note
 Contains no other ingredients (≅ 0,1%) that are classified as hazardous to health or the environment according to the current knowledge of the supplier and must be mentioned in this section.
 The wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information** Remove contaminated, saturated clothing immediately.
- **After inhalation**
 Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
 In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact**
 Instantly wash with water and soap and rinse thoroughly.
 If skin irritation continues, consult a doctor.
- **After eye contact**
 Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing** Do not induce vomiting; instantly call for medical help.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents** Water.
- **5.2 Special hazards arising from the substance or mixture**
 Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazards.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information**
 Cool closed containers exposed to fire with water.
 Do not allow run-off from fire fighting to enter drains or water courses.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Remove all sources of ignition. Provide adequate ventilation. Refer to protective measurer, listed in sections 7 and 8.
- **6.2 Environmental precautions:**
Do not allow product to enter into sewerage systems or water bodies.
Inform respective authorities in case of product reaches water or sewage systems.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at working place.
Keep containers tightly sealed.
- **Information about protection against explosions and fires:**
Protect against electrostatic charges.
Keep ignition sources away - Do not smoke.
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixture with air.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by warehouses and containers:** Store only in the original container.
- **Information about storage in one common storage facility:**
Keep away from foodstuffs, beverages and food.
- **Further information about storage conditions:** Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical systems:**
Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.
- **Components with critical values that require monitoring at the workplace:**

108-65-6 2-methoxy-1-methylethyl acetate

WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
IOELV (European Union)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 4)

107-98-2 1-methoxypropan-2-ol

WEL (Great Britain)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
IOELV (European Union)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Skin

· DNELs

1174522-20-3 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics*

Oral	DNEL	300 mg/kg/day (General population, long-term exposure)
Dermal	DNEL	300 mg/kg/day (General population, long-term exposure) 300 mg/kg/day (Workers, long-term exposure)
Inhalative	DNEL	900 mg/m ³ (General population, long-term exposure) 1,500 mg/m ³ (Workers, long-term exposure)

7440-50-8 copper

Dermal	DNEL	137 mg/kg/day (Workers, long-term exposure) 273 mg/kg/day (Workers, short-term exposure) 273 mg/kg/day (General population, short-term exposure)
Inhalative	DNEL	20 mg/m ³ (Workers, short-term exposure) 20 mg/m ³ (General population, short-term exposure)

107-98-2 1-methoxypropan-2-ol

Oral	DNEL	3.3 mg/kg/day (General population, long-term exposure)
Dermal	DNEL	18.1 mg/kg/day (General population, long-term exposure) 50.6 mg/kg/day (Workers, long-term exposure)
Inhalative	DNEL	43.9 mg/m ³ (General population, long-term exposure) 369 mg/m ³ (Workers, long-term exposure) 553.5 mg/m ³ (Workers, short-term exposure)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	DNEL	1.6 mg/kg/day (General population, long-term exposure)
Dermal	DNEL	54.8 mg/kg/day (General population, long-term exposure) 153.5 mg/kg/day (Workers, long-term exposure)
Inhalative	DNEL	33 mg/m ³ (General population, long-term exposure) 275 mg/m ³ (Workers, long-term exposure)

7440-66-6 zinc powder -zinc dust (stabilized)

Oral	DNEL	0.83 mg/kg/day (General population, long-term exposure)
Dermal	DNEL	83 mg/kg/day (General population, long-term exposure) 83 mg/kg/day (Workers, long-term exposure)
Inhalative	DNEL	2.5 mg/m ³ (General population, long-term exposure) 5 mg/m ³ (Workers, long-term exposure)

· PNECs

7440-50-8 copper

PNEC	0.0052 mg/L (marine water) 0.0078 mg/L (freshwater)
------	--

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 5)

PNEC	65.5 mg/kg (soil) 676 mg/kg (sediment (marine water)) 87 mg/kg (sediment (freshwater))
------	--

107-98-2 1-methoxypropan-2-ol

PNEC	100 mg/L (sewage treatment plant) 1 mg/L (marine water) 10 mg/L (freshwater)
PNEC	2.47 mg/kg (soil) 4.17 mg/kg (sediment (marine water)) 41.6 mg/kg (sediment (freshwater))

108-65-6 2-methoxy-1-methylethyl acetate

PNEC	100 mg/L (sewage treatment plant) 0.0635 mg/L (marine water) 0.635 mg/L (freshwater)
PNEC	0.29 mg/kg (soil) 0.329 mg/kg (sediment (marine water)) 3.29 mg/kg (sediment (freshwater))

7440-66-6 zinc powder -zinc dust (stabilized)

PNEC	0.0061 mg/L (marine water) 0.0206 mg/L (freshwater)
PNEC	35.6 mg/kg (soil) 56.5 mg/kg (sediment (marine water)) 117.8 mg/kg (sediment (freshwater))

- **Additional information:** The valid lists during the compilation were used as data basis.
- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**
Instantly remove any spoiled and impregnated garments.
After skin contact clean with water and soap or use appropriate detergents . Do not use organic solvent.
Keep away from foodstuffs, beverages and food.
- **Breathing equipment:**
In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus, independent of circulating air.
Filter A/P2.
- **Protection of hands:**
The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Barrier creams may help to protect the exposed areas of the skin.
- **Material of gloves**
Nitrile rubber or fluorine rubber (0.4 mm). Breakthrough time> 480min with full contact. Notice., The information provided by the glove manufacturer to permeability and breakthrough times and the specific workplace conditions When cracking or change in color, shape or elasticity, the gloves should be changed immediately.
- **Eye protection:** Tightly sealed safety glasses.

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 6)

· **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Fluid
· Colour:	Gold coloured
· Smell:	Benzen-like
· Odour threshold:	Not determined.

· **pH-value:**

Initial boiling point and boiling range: 119 °C

· **Flash point:** 35 °C (DIN/ISO 3679halten
23 Ga)

· **Inflammability (solid, gaseous)** Not applicable.

· **Ignition temperature:** 200 °C

· **Decomposition temperature:** Not determined.

· **Self-inflammability:** Product is not self-igniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/steam mixtures is possible.

· **Critical values for explosion:**

· Lower:	0.6 Vol %
· Upper:	11.0 Vol %

· **Steam pressure at 20 °C:** 10.8 hPa

· **Density at 20 °C** 1,060-1.217 g/cm³ (DIN 51757)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix

· **Viscosity:**

dynamic: Not determined.

kinematic at 20 °C: 70 s (DIN 53211/4)

· **or at 20 °C:** 47 s (ISO 2431-1993/6 mm)

· **Solvent content:**

Organic solvents: 53-54 %

Water: 0.0 %

VOC (EG) 560-600 g/l

Solids content: 46-47 %

· **9.2 Other information**

No further relevant information available.

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 7)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Strong oxidizing agent.
Strong acids and bases
- **10.6 Hazardous decomposition products:**
such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
There are no data available on the preparation itself.
The mixture is classified under Regulation No 1272/2008 = CLP (EU-GHS) Regulation and the toxicological hazards. See Section 3 and 15 for details.

- **LD/LC50 values that are relevant for classification:**

1174522-20-3 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics*

Oral	LD50	>15,000 mg/kg (rat (Ratte))
Dermal	LD50	>3,000 mg/kg (kan)

107-98-2 1-methoxypropan-2-ol

Oral	LD50	>5,000 mg/kg (rat (Ratte))
Dermal	LD50	13,500 mg/kg (rabbit (Kaninchen))

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	>8,532 mg/kg (rat (Ratte))
Dermal	LD50	>5,000 mg/kg (rat (Ratte))
Inhalative	LC50/4 h	35.7 mg/l (rat (Ratte))
	LC50/6 h	>23.8 mg/l (rat (Ratte))

7440-66-6 zinc powder -zinc dust (stabilized)

Oral	LD50	>2,000 mg/kg (rat (Ratte))
Inhalative	LC50/4 h	>5.41 mg/l (rat (Ratte))

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Other observations:**
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system.
Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
The liquid splashed in the eyes may cause irritation and reversible damage.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 8)

- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

107-98-2 1-methoxypropan-2-ol

LC50/96h	>4,000 mg/l (Leuciscus idus(Goldorfe)) (Fische) 20,800 mg/l (Pimephales promelas (Elritze)) (Fische)
EC50/48h	>100 mg/l (wfl) (Daphnien)
LC/EC50 (72 h)	>100 mg/l (algae, different)

108-65-6 2-methoxy-1-methylethyl acetate

LC50/96h	100-180 mg/l (Onchorhynchus mykiss (Regenbogenforelle)) (Fische)
EC50/48h	>500 mg/l (daphnia magna (Wasserfloh)) (Daphnien)

7440-66-6 zinc powder -zinc dust (stabilized)

LC50/96h	0.238 mg/l (Pimephales promelas (Elritze))
EC50/48h	0.356 mg/l (wfl)
EC50/72h	0.106 mg/l (Desmodesmus subspicatus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:** CAS 7440-50-8 Kupfer: M-Faktor = 10
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
Water danger class 3 (Self-assessment): extremely hazardous for water.
Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into soil.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed of together with household garbage. Do not allow product to enter into sewage systems.
Hand over to disposers of hazardous waste.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 9)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1263

- **14.2 UN proper shipping name**
- **ADR** 1263 PAINT, ENVIRONMENTALLY HAZARDOUS
- **IMDG** PAINT (copper, zinc powder -zinc dust
- **IATA** (stabilized)), MARINE POLLUTANT
- **IATA** PAINT

· **14.3 Transport hazard class(es)**

· **ADR**



- **Class** 3 (F1) Flammable liquids.
- **Label** 3

· **IMDG**



- **Class** 3 Flammable liquids.
- **Label** 3

· **IATA**



- **Class** 3 Flammable liquids.
- **Label** 3

- **14.4 Packing group**
- **ADR, IMDG, IATA** III

- **14.5 Environmental hazards:** Product contains environmentally hazardous substances: copper
- **Marine pollutant:** Yes
- **Special marking (ADR):** Symbol (fish and tree)
- **Special marking (ADR):** Symbol (fish and tree)

- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Kemler Number:** 30
- **EMS Number:** F-E,S-E

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 10)

· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· Transport in accordance with ADR/RID, IMDG and ICAO/IATA.	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
E1 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations**
- **Water hazard class:** Water danger class 3 (Self-assessment): extremely hazardous for water.
- **Other regulations, limitations and prohibitive regulations**
- **VOC value EC %:** <57.22 %
- **VOC (EU)** <606.6 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The information of this SDS is based on the present state of our knowledge and on current EU and national laws. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product : it is not

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.06.2021

version: 14

Revision: 07.06.2021

Trade name REVELL EMAIL COLOR
No. 92,93,94,95

(Contd. of page 11)

to be considered as a guarantee of the products' properties.

· **Relevant phrases**

Danger notes of the contents substances listed under item 3.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· **Classification according to Regulation (EC) No 1272/2008**

Physical hazard: Flash point (° C)

Health and environmental hazards: calculation method

· **Department issuing data specification sheet:** department product safety

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Sol. 1: Flammable solids – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

Paragraphs, which were changed compared to the former version, are marked with "***" on the left margin.